

Beginning Macros

Prepared by



**Global Business Intelligence
Consulting and Training**

Destiny Corporation
100 Great Meadow Rd Suite 601
Wethersfield, CT 06109-2379
Phone: (860) 721-1684 1-800-7TRAINING Fax: (860)
721-9784
Email: info@destinycorp.com
Web: www.destinycorp.com

Introduction to Macros in SAS

Why learn macros? In brief, they provide the only solution to certain programming goals. Further, they greatly reduce the amount of work required to achieve some goals. These facts will become clear as the curriculum continues.

Macros are used to:

- Change code easily, making code more flexible.
- Conditionally generate and execute code.
- Generate repetitive code.
- Pass variable information across Step boundaries.

A macro is stored text that can be referenced (or "called") using another, shorter name. In effect the macro environment allows the programmer to take one set of text and convert it to another text string according to well defined rules.

The macro environment allows a programmer to write customized syntax, which can be reused whole or modified with different parameters to produce varied output. Macros allow the programmer to set different values for data sets, variables, statistics, etc. each time the syntax runs. Rather than sift through hundreds of lines of code to find and change select references, the macro is coded with parameters, which need to be changed once each time the syntax runs.

As one example of where macros might be used consider the situation where you wish to include a summary statistic, such as average salary, in a title statement. The average salary could be stored in a data set, but how would the title pick up the value? Alternatively, the programmer could 'hard code' the value into the title. But what happens if the data set values for salary change? The programmer would have to be involved interactively every time the program runs. Hardly satisfactory!

In contrast, the value of average salary could be saved as a macro variable. The title statement can then reference the macro variable which would resolve to the value of average salary.

Macro Variables

In this module, we discuss two special characters:

- ampersand (&)
- percent (%).

Both characters have special functionality within the macro environment.

Naming conventions are to be followed for macro names, macro bundle names, and parameter names. Although these terms are still undefined, bear in mind the following when assigning names:

- Any valid SAS name according to the Operating System and SAS version is generally acceptable
- SAS has reserved some names for other use. Do not use the following words when programming in macros:

ABEND	ABORT	ACT	ACTIVATE	BQUOTE
BY	CLEAR	CLOSE	CMS	COMANDR
COPY	DEACT	DEL	DELETE	DISPLAY
DMIDSPY	DMISPLIT	DO	EDIT	ELSE
END	EVAL	FILE	GLOBAL	GO
GOTO	IF	INC	INCLUDE	INDEX
INFILE	INPUT	KEYDEF	LENGTH	LET
LIST	LISTM	LOCAL	MACRO	MEND
METASYM	NRBQUOTE	NRQUOTE	NRSTR	ON
OPEN	PAUSE	PUT	QSCAN	QSUBSTR
QUOTE	QUPCASE	RESOLVE	RETURN	RUN
SAVE	SCAN	STOP	STR	SUBSTR
SUPERQ	SYSEXEC	SYSGET	SYSRPUT	THEN
TO	TSO	UNQUOTE	UNSTR	UNTIL
UPCASE	WHILE	WINDOW		

An attempt to call a macro by a reserved name will result in a warning message. The macro will be neither compiled nor available for use.

%Let Statements

A %let statement is one method used to create a macro variable. Within a %let statement the name of the macro variable is to the left of the equal sign. Everything to the right of the equal sign up to but not including the semi-colon, except leading and trailing blanks, is the value of the macro variable. We will discuss the %let statement in greater detail in a subsequent chapter.

We wish to consider the following example to demonstrate use of the ampersand and percent symbols.

```
Command window
00001 %let ds=denogius;
00002
00003 proc sort data=denogius;
00004   by gender;
00005 run;
00006
00007 title 'Print of Sorted data set';
00008
00009 proc print data=denogius;
00010   by gender;
00011 run;
```

Line	Comment
00001	Define a macro variable called ds with its value. The presence of a % followed by a non-blank character triggers the macro facility. A %let tells the macro facility that a macro variable is to be defined. The %let statement can appear anywhere within a SAS program to define one macro variable at a time.
00003 00009	Use &ds (ampersand+macro variable name) to invoke the value.

When the SAS Supervisor sees an ampersand followed by a non-blank character, the macro facility is activated. In turn, the macro facility determines the value for the macro variable and passes the value back on to the input stack.

A partial listing of the output is displayed below.

Print of Sorted data set

Obs	staffno	name	age	height	weight	status	child
1	0052	Julia Pendlebury	21	63.0	52	M	2
2	0058	Norman Harvey	22	54.0	52	S	1
3	0012	Mary Holmesworth	26	65.0	75	D	1
4	0084	Helen Clinderford	31	67.0	89	M	0
5	0038	Jennifer Dawson	36	63.0	71	M	1
6	0021	Shirley Walters	40	66.0	81	M	2
7	0085	Dawn Duvet	42	74.0	88	M	3
8	0071	Dorothy Belling	46	69.0	72	P	3
9	0074	Joanne Kinderly	49	71.0	79	M	1

The code executes as if the programmer had submitted the following:

```

Command ===>
*****
00001 proc sort data=saved.dsn out=work.dsn;
00002 by gender;
00003 run;
00004 title 'Print of Sorted data set';
00005 proc print data=work.dsn;
00006 by gender;
00007 run;
*****

```

What is the advantage of using the macro %let statement over direct coding? Consider how easily changes can be made should a new data set be used. It would also be easy to use a different By variable in the By statement.

The following program shows easy code changes with macros.

```

Command ===>
*****
00001 %let ds = Computer;
00002 %let byvar = type;
00003
00004 proc sort data=saved.dsn out=work.dsn;
00005 by &byvar;
00006 run;
00007
00008 title 'Print of Sorted Data Set';
00009
00010 proc print data=work.dsn;
00011 by &byvar;
00012 run;
*****

```

Line	Comment
00001	The %let statements now refer to an entirely
00002	different data set and By variable.

A partial listing of the new output is displayed below.

Print of Sorted data set

Obs	CATNUM	SUPPLIER	CPU	DISK	WHOLESALE
1	1	FLOPPY COMPUTERS	286	20	550
2	2	FLOPPY COMPUTERS	286	40	600
3	3	FLOPPY COMPUTERS	286	100	750
4	4	FLOPPY COMPUTERS	386SX	40	750
5	5	FLOPPY COMPUTERS	386SX	100	950
6	6	FLOPPY COMPUTERS	386DX	40	950
7	7	FLOPPY COMPUTERS	386DX	100	1250
8	8	FLOPPY COMPUTERS	486SX	40	1350
9	9	FLOPPY COMPUTERS	486SX	100	1550

Macro Variables Within Title or Footnote Statements

Let us now enclose the title statement within single quotes. This will cause the macro within the title to not resolve properly.

```

Command ===>
*****
00001 %let ds=computer;
00002 %let byvar = type;
00003
00004 proc sort data=saved.dsn out=work.dsn;
00005 by &byvar;
00006 run;
00007
00008 title 'Print of the data set &ds';
00009
00010 proc print data=work.dsn;
00011 by &byvar;
00012 run;
*****

```

Line	Comment
00008	The title statement includes a call to macro ds.

Print of the data set &ds

Obs	CATNUM	SUPPLIER	CPU	DISK	WHOLESALE
1	1	FLOPPY COMPUTERS	286	20	550
2	2	FLOPPY COMPUTERS	286	40	600
3	3	FLOPPY COMPUTERS	286	100	750
4	4	FLOPPY COMPUTERS	386SX	40	750
5	5	FLOPPY COMPUTERS	386SX	100	950
6	6	FLOPPY COMPUTERS	386SX	40	950
7	7	FLOPPY COMPUTERS	386DX	100	1250
8	8	FLOPPY COMPUTERS	486SX	40	1350
9	9	FLOPPY COMPUTERS	486SX	100	1550

The Output shows that the title statement still reads 'Print of the data set &ds'.

In other words, within the title statement &ds did not resolve to 'Computer' as expected. Elsewhere within the program &ds resolved appropriately.

A check of the Log shows no syntax errors.

```

Command ===>
*****
00001 %let ds=computer;
00002 %let byvar=type;
00003
00004 proc sort data=saved.dsn out=work.dsn;
00005 by &byvar;
00006 run;
*****
NOTE: There were 36 observations read from the data set WORK.COMPUTER.
NOTE: The data set WORK.COMPUTER has 36 observations and 7 variables.
NOTE: PROCEDURE SORT used:
      real time    0.06 seconds
      cpu time     0.06 seconds
*****
00007
00008 title 'Print of the data set &ds';
00009
00010 proc print data=work.dsn;
00011 by &byvar;
00012 run;
*****
NOTE: There were 36 observations read from the data set WORK.COMPUTER.
NOTE: PROCEDURE PRINT used:
      real time    0.01 seconds
      cpu time     0.01 seconds
*****

```

This is one of the few times SAS distinguishes between single quotes (as used in the above program) and double quotes.

In brief:

- Use double quotes (or no quotes for titles and footnotes) if you want the macro to resolve.
- To let the ampersand remain – as with R&D – use single quotes

Refer now to the program with both options used properly.

```

1
Command ===>
00001 Xlet ds = Computer;
00002 Xlet byvar = type;
00003
00004 proc sort data=saved.sds out=work.sds;
00005   by byvar;
00006 run;
00007
00008 title1 "Print of the data set sds";
00009 title2 "Results of Current R&D";
00010
00011 proc print data=work.sds;
00012   by byvar;
00013 run;
00014

```

Line	Comment
00008	The title1 statement includes a call to macro ds. The macro will be resolved because the title statement uses <u>double quotes</u> . The same usage for double quotes applies to footnote statements.
00009	The title2 statement includes &D. SAS will not attempt to resolve it as a macro D because the title statement is in <u>single quotes</u> . The same usage for single quotes applies to footnote statements.

% Output (Untitled)

Command ===> |

Print of the data set computer
Results of Current R&D

----- TYPE=DESKTOP -----

Obs	CATNUM	SUPPLIER	CPU	DISK	WHOLESALE
1	1	FLOPPY COMPUTERS	286	20	550
2	2	FLOPPY COMPUTERS	286	40	600
3	3	FLOPPY COMPUTERS	286	100	750
4	4	FLOPPY COMPUTERS	386SX	40	750
5	5	FLOPPY COMPUTERS	386SX	100	950
6	6	FLOPPY COMPUTERS	386DX	40	950
7	7	FLOPPY COMPUTERS	386DX	100	1250
8	8	FLOPPY COMPUTERS	486SX	40	1350

What would happen if we placed the title2 statement in double quotes? How would SAS handle the request to resolve the macro D? The answer depends on a few different parameters.

- First, if previous coding had already defined a macro variable D, SAS would place its value into the title string.
- Second, if no macro variable D had been defined, SAS would leave the title string unresolved – Demonstration of Recent R&D – while giving a Warning message in the log.

If the macro facility fails to find the current value for a macro variable, the following message appears on the SAS Log:

Warning: Apparent symbolic reference is not resolved.

SAS refers to macro variables as 'symbolics'. The Warning message states that the macro has been resolved.

Symbolgen

The global option *Symbolgen* is one of several tools available which make it possible to examine the values of macros as they are processed. Consider the following example in which the previous code is run with this option in effect.

```

Command Editor (Untitled)
Command ===>
00001 options symbolgen;
00002
00003 Xlet ds=computer;
00004 Xlet byvar=type;
00005
00006 proc sort data=saved.sds out=work.sds;
00007   by byvar;
00008 run;
00009
00010 title1 "Print of the data set sds";
00011 title2 "Results of Current R&D";
00012
00013 proc print data=work.sds;
00014   by byvar;
00015 run;

```

The log displays the resolved values of macros as the code is processed. This can be a useful aid in debugging a program.

```

Log (Untitled)
Command ===>
31 options symbolgen;
32
33 Xlet ds=Computer;
34
35 Xlet byvar=type;
36
37
37 proc sort data=saved.sds out=work.sds;
SYMBOLGEN: Macro variable DS resolves to Computer
SYMBOLGEN: Macro variable DS resolves to Computer
SYMBOLGEN: Macro variable BYVAR resolves to type
38   by byvar;
39 run;

```

This option stays in effect until it is turned off.

```

Command Editor (Untitled)
Command ===>
00001 options nosymbolgen;
00002

```

%Put Statement

A *%put* statement will write up to 132 characters of text to the log as well as the resolved value of a macro. This too can be useful in debugging a program or just as a tool to see the value of a macro.

For instance, we could examine the values of the macros ds and byvar with the following code:

```

Command Editor (Untitled)
Command ===>
00001 %put Value of ds= &ds;
00002
00003 %put Value of By variable= &byvar;
00004

```

```

Log (Untitled)
Command ===>
34 %put Value of ds= &ds;
Value of ds= computer
35
36 %put Value of By variable= &byvar;
Value of By variable= type

```

Data vs. Macro Variables

It is important to realize that macro variables are not the same as data set variables.

How are macro variables different from data set variables?

- They are created differently from data set variables.
- They are stored in symbol tables, not data sets.
- A macro variable has a single value whereas a data set variable can have multiple values depending on the loop of the data.

Creating Data Set Variables and Macro Variables

SAS can make a data set variable in many ways by using different syntax options within the Data Step.

```

Program Editor code1
Command ==>
00001 data work.new;
00002   length title1 $ 4;
00003   set saved.demog;
00004   if gender = "M" then do;
00005     title1="Mr.";
00006     title2="Sir";
00007   end;
00008   else if status in ("S","D") then title1 = "Ms.";
00009   else title1 = "Mrs.";
00010 run;
00011
00012 proc print data=work.new(obs=5);
00013   var name gender title1 title2;
00014 run;

```

Line	Comment
00002	The length statement creates space in the PDV for a new data set variable.
00003	The Set statement reads the SAS data set saved.demog
00004-00009	The variables <i>title1</i> and <i>title2</i> are created by assignment.

Although at this point we have only discussed one technique, the `%let` statement, there are several ways in which macro variables can be created. Three techniques are illustrated in the following example.

```

Command ==>
00001 %let dsvar = Monday;
00002
00003 data _null_;
00004   call symput ('day', 'Tuesday');
00005 run;
00006
00007 proc sql noprint;
00008   select mean(age)
00009   into : mshage
00010   from saved.demog1us;
00011 quit;
00012

```

Line	Comment
00001	The <code>%let</code> statement creates macro variable <i>mvar</i> .
00004	The <code>Call Symput</code> routine creates macro variable <i>day</i> .
00009	The Proc SQL <code>into clause</code> creates macro variable <i>meanage</i> .

The point to remember: the syntax determines what is being created! There is no ambiguous case between a data set variable and a macro variable.

Where the Variables and Values Reside

Data set variables and macro variables can have the same name.

They will never replace each other's values, however.

They live in different structures (a symbol table vs. a data set or the PDV) and they are called for in different ways.

```

Command ==>
00001 %let day = Friday;
00002 %put &day;
00003
00004 proc print data=sashelp.usarea (drop=offset);
00005   title "Print of Macro Variable";
00006   where scope = "GLOBAL" and name = 'DAY';
00007 run;
00008
00009 /* VERSUS */
00010
00011 data hender;
00012   day="Saturday";
00013   put day;
00014 run;
00015 proc print data=work.hender;
00016   title "Print of Data Set Variable";
00017 run;
00018 title;
00019

```

Line	Comment
	The Macro Variable <i>DAY</i>
00001	The <code>%let</code> statement defines macro variable <i>day</i> as <i>Friday</i> .
00002	The <code>%put</code> shows the value of macro variable <i>day</i> in the Log.
00004-00007	The Proc Print of sashelp.vmacro shows the macro variable in the Output window.
	The Data Set Variable <i>DAY</i>
00012	The data set character variable <i>day</i> is created through assignment.
00013	The Put statement shows the data set variable value in the Log.
00015-00017	The Proc Print of the data set shows the data set value of <i>day</i> .

Later, we will see how to pass a data set variable value directly into a macro variable.

Summary

- To define a macro variable, use the following syntax:

```
%let <macro_variable> = <value>;
```

Example:

```
%let ds = demogrf;
```

- To use a macro variable, precede the macro variable name with an ampersand (&)

Example:

```
Proc print data = &ds;
```

- If the macro variable is to be used in quotes, as in a title, be sure to use double quotes to get the value to resolve.

```
Title "Report of Data Set &ds";
```

- Use the global option `symbolgen` to see the resolved values of macros in the log.
- Use a `%put` statement to write the resolved value of a macro to the log:

```
%put The value of the macro = &ds;
```

Differences between data set variables and macro variables:

- Data set variables exist in data sets; macro variables exist in symbol tables.
- Data set variables are created only in data steps or proc steps; macro variables can be created with statements such as `%let` that are not part of a step.
- A data set variable can have multiple values, whereas a macro variable can have only one value.
- To get the value of a data set variable, you just use the name of the variable; to resolve a macro variable, you must precede the name of the variable with an ampersand (&)

Automatic Macro Variables

Invoking SAS creates a set of automatic macro variables (assuming that SAS system options enable the macro facility).

These macro variables and their values are held in the Automatic Symbol Table (AST). The AST and its variables can only be deleted by exiting out of SAS.

The automatic macro variables exhibit some distinct features:

The values are set at the start of the SAS session. Therefore, the automatic macro variables *sysdate*, *sysstime*, and *sysday* are set when launching SAS.

Some automatic macro variables – such as *sysdate*, *sysstime*, and *sysday* – are read only (R/O) and therefore cannot be changed by the programmer.

Some automatic macro variables are read-write (R/W). These can be changed by the programmer.

Determining the Values of Automatic SAS Variables

Automatic macro variables can be viewed using any of the following three syntax options.

Option 1

```
Command >>>
00001 proc print data=sashelp.vmacro;
00002   where scope = "AUTOMATIC";
00003 run;
00004
```

Line	Comment
00002	The variable "scope" refers to the referencing environment or table. To see other variables, use "USER", "LOCAL", "GLOBAL" in place of "AUTOMATIC"

Line	Scope	Name	Offset	Value
1	AUTOMATIC	AFPSID	0	0
2	AUTOMATIC	AFPSNAME	0	0
3	AUTOMATIC	APLID	0	0
4	AUTOMATIC	APSTR1	0	0
5	AUTOMATIC	APSTR2	0	0
6	AUTOMATIC	APSTR3	0	0
7	AUTOMATIC	APSTR4	0	0
8	AUTOMATIC	APSTR5	0	0
9	AUTOMATIC	APSTR6	0	0
10	AUTOMATIC	APSTR7	0	0
11	AUTOMATIC	APSTR8	0	0
12	AUTOMATIC	APSTR9	0	0
13	AUTOMATIC	APSTR10	0	0
14	AUTOMATIC	APSTR11	0	0
15	AUTOMATIC	APSTR12	0	0
16	AUTOMATIC	APSTR13	0	0
17	AUTOMATIC	APSTR14	0	0
18	AUTOMATIC	APSTR15	0	0
19	AUTOMATIC	APSTR16	0	0
20	AUTOMATIC	APSTR17	0	0
21	AUTOMATIC	APSTR18	0	0
22	AUTOMATIC	APSTR19	0	0
23	AUTOMATIC	APSTR20	0	0
24	AUTOMATIC	APSTR21	0	0
25	AUTOMATIC	APSTR22	0	0
26	AUTOMATIC	APSTR23	0	0
27	AUTOMATIC	APSTR24	0	0
28	AUTOMATIC	APSTR25	0	0
29	AUTOMATIC	APSTR26	0	0
30	AUTOMATIC	APSTR27	0	0
31	AUTOMATIC	APSTR28	0	0
32	AUTOMATIC	APSTR29	0	0
33	AUTOMATIC	APSTR30	0	0
34	AUTOMATIC	APSTR31	0	0
35	AUTOMATIC	APSTR32	0	0
36	AUTOMATIC	APSTR33	0	0
37	AUTOMATIC	APSTR34	0	0
38	AUTOMATIC	APSTR35	0	0
39	AUTOMATIC	APSTR36	0	0
40	AUTOMATIC	APSTR37	0	0
41	AUTOMATIC	APSTR38	0	0
42	AUTOMATIC	APSTR39	0	0
43	AUTOMATIC	APSTR40	0	0
44	AUTOMATIC	APSTR41	0	0
45	AUTOMATIC	APSTR42	0	0
46	AUTOMATIC	APSTR43	0	0
47	AUTOMATIC	APSTR44	0	0
48	AUTOMATIC	APSTR45	0	0
49	AUTOMATIC	APSTR46	0	0
50	AUTOMATIC	APSTR47	0	0
51	AUTOMATIC	APSTR48	0	0
52	AUTOMATIC	APSTR49	0	0
53	AUTOMATIC	APSTR50	0	0
54	AUTOMATIC	APSTR51	0	0
55	AUTOMATIC	APSTR52	0	0
56	AUTOMATIC	APSTR53	0	0
57	AUTOMATIC	APSTR54	0	0
58	AUTOMATIC	APSTR55	0	0
59	AUTOMATIC	APSTR56	0	0
60	AUTOMATIC	APSTR57	0	0
61	AUTOMATIC	APSTR58	0	0
62	AUTOMATIC	APSTR59	0	0
63	AUTOMATIC	APSTR60	0	0
64	AUTOMATIC	APSTR61	0	0
65	AUTOMATIC	APSTR62	0	0
66	AUTOMATIC	APSTR63	0	0
67	AUTOMATIC	APSTR64	0	0
68	AUTOMATIC	APSTR65	0	0
69	AUTOMATIC	APSTR66	0	0
70	AUTOMATIC	APSTR67	0	0
71	AUTOMATIC	APSTR68	0	0
72	AUTOMATIC	APSTR69	0	0
73	AUTOMATIC	APSTR70	0	0
74	AUTOMATIC	APSTR71	0	0
75	AUTOMATIC	APSTR72	0	0
76	AUTOMATIC	APSTR73	0	0
77	AUTOMATIC	APSTR74	0	0
78	AUTOMATIC	APSTR75	0	0
79	AUTOMATIC	APSTR76	0	0
80	AUTOMATIC	APSTR77	0	0
81	AUTOMATIC	APSTR78	0	0
82	AUTOMATIC	APSTR79	0	0
83	AUTOMATIC	APSTR80	0	0
84	AUTOMATIC	APSTR81	0	0
85	AUTOMATIC	APSTR82	0	0
86	AUTOMATIC	APSTR83	0	0
87	AUTOMATIC	APSTR84	0	0
88	AUTOMATIC	APSTR85	0	0
89	AUTOMATIC	APSTR86	0	0
90	AUTOMATIC	APSTR87	0	0
91	AUTOMATIC	APSTR88	0	0
92	AUTOMATIC	APSTR89	0	0
93	AUTOMATIC	APSTR90	0	0
94	AUTOMATIC	APSTR91	0	0
95	AUTOMATIC	APSTR92	0	0
96	AUTOMATIC	APSTR93	0	0
97	AUTOMATIC	APSTR94	0	0
98	AUTOMATIC	APSTR95	0	0
99	AUTOMATIC	APSTR96	0	0
100	AUTOMATIC	APSTR97	0	0
101	AUTOMATIC	APSTR98	0	0
102	AUTOMATIC	APSTR99	0	0
103	AUTOMATIC	APSTR100	0	0
104	AUTOMATIC	APSTR101	0	0
105	AUTOMATIC	APSTR102	0	0
106	AUTOMATIC	APSTR103	0	0
107	AUTOMATIC	APSTR104	0	0
108	AUTOMATIC	APSTR105	0	0
109	AUTOMATIC	APSTR106	0	0
110	AUTOMATIC	APSTR107	0	0
111	AUTOMATIC	APSTR108	0	0
112	AUTOMATIC	APSTR109	0	0
113	AUTOMATIC	APSTR110	0	0
114	AUTOMATIC	APSTR111	0	0
115	AUTOMATIC	APSTR112	0	0
116	AUTOMATIC	APSTR113	0	0
117	AUTOMATIC	APSTR114	0	0
118	AUTOMATIC	APSTR115	0	0
119	AUTOMATIC	APSTR116	0	0
120	AUTOMATIC	APSTR117	0	0
121	AUTOMATIC	APSTR118	0	0
122	AUTOMATIC	APSTR119	0	0
123	AUTOMATIC	APSTR120	0	0
124	AUTOMATIC	APSTR121	0	0
125	AUTOMATIC	APSTR122	0	0
126	AUTOMATIC	APSTR123	0	0
127	AUTOMATIC	APSTR124	0	0
128	AUTOMATIC	APSTR125	0	0
129	AUTOMATIC	APSTR126	0	0
130	AUTOMATIC	APSTR127	0	0
131	AUTOMATIC	APSTR128	0	0
132	AUTOMATIC	APSTR129	0	0
133	AUTOMATIC	APSTR130	0	0
134	AUTOMATIC	APSTR131	0	0
135	AUTOMATIC	APSTR132	0	0
136	AUTOMATIC	APSTR133	0	0
137	AUTOMATIC	APSTR134	0	0
138	AUTOMATIC	APSTR135	0	0
139	AUTOMATIC	APSTR136	0	0
140	AUTOMATIC	APSTR137	0	0
141	AUTOMATIC	APSTR138	0	0
142	AUTOMATIC	APSTR139	0	0
143	AUTOMATIC	APSTR140	0	0
144	AUTOMATIC	APSTR141	0	0
145	AUTOMATIC	APSTR142	0	0
146	AUTOMATIC	APSTR143	0	0
147	AUTOMATIC	APSTR144	0	0
148	AUTOMATIC	APSTR145	0	0
149	AUTOMATIC	APSTR146	0	0
150	AUTOMATIC	APSTR147	0	0
151	AUTOMATIC	APSTR148	0	0
152	AUTOMATIC	APSTR149	0	0
153	AUTOMATIC	APSTR150	0	0
154	AUTOMATIC	APSTR151	0	0
155	AUTOMATIC	APSTR152	0	0
156	AUTOMATIC	APSTR153	0	0
157	AUTOMATIC	APSTR154	0	0
158	AUTOMATIC	APSTR155	0	0
159	AUTOMATIC	APSTR156	0	0
160	AUTOMATIC	APSTR157	0	0
161	AUTOMATIC	APSTR158	0	0
162	AUTOMATIC	APSTR159	0	0
163	AUTOMATIC	APSTR160	0	0
164	AUTOMATIC	APSTR161	0	0
165	AUTOMATIC	APSTR162	0	0
166	AUTOMATIC	APSTR163	0	0
167	AUTOMATIC	APSTR164	0	0
168	AUTOMATIC	APSTR165	0	0
169	AUTOMATIC	APSTR166	0	0
170	AUTOMATIC	APSTR167	0	0
171	AUTOMATIC	APSTR168	0	0
172	AUTOMATIC	APSTR169	0	0
173	AUTOMATIC	APSTR170	0	0
174	AUTOMATIC	APSTR171	0	0
175	AUTOMATIC	APSTR172	0	0
176	AUTOMATIC	APSTR173	0	0
177	AUTOMATIC	APSTR174	0	0
178	AUTOMATIC	APSTR175	0	0
179	AUTOMATIC	APSTR176	0	0
180	AUTOMATIC	APSTR177	0	0
181	AUTOMATIC	APSTR178	0	0
182	AUTOMATIC	APSTR179	0	0
183	AUTOMATIC	APSTR180	0	0
184	AUTOMATIC	APSTR181	0	0
185	AUTOMATIC	APSTR182	0	0
186	AUTOMATIC	APSTR183	0	0
187	AUTOMATIC	APSTR184	0	0
188	AUTOMATIC	APSTR185	0	0
189	AUTOMATIC	APSTR186	0	0
190	AUTOMATIC	APSTR187	0	0
191	AUTOMATIC	APSTR188	0	0
192	AUTOMATIC	APSTR189	0	0
193	AUTOMATIC	APSTR190	0	0
194	AUTOMATIC	APSTR191	0	0
195	AUTOMATIC	APSTR192	0	0
196	AUTOMATIC	APSTR193	0	0
197	AUTOMATIC	APSTR194	0	0
198	AUTOMATIC	APSTR195	0	0
199	AUTOMATIC	APSTR196	0	0
200	AUTOMATIC	APSTR197	0	0
201	AUTOMATIC	APSTR198	0	0
202	AUTOMATIC	APSTR199	0	0
203	AUTOMATIC	APSTR200	0	0
204	AUTOMATIC	APSTR201	0	0
205	AUTOMATIC	APSTR202	0	0
206	AUTOMATIC	APSTR203	0	0
207	AUTOMATIC	APSTR204	0	0
208	AUTOMATIC	APSTR205	0	0
209	AUTOMATIC	APSTR206	0	0
210	AUTOMATIC	APSTR207	0	0
211	AUTOMATIC	APSTR208	0	0
212	AUTOMATIC	APSTR209	0	0
213	AUTOMATIC	APSTR210	0	0
214	AUTOMATIC	APSTR211	0	0
215	AUTOMATIC	APSTR212	0	0
216	AUTOMATIC	APSTR213	0	0
217	AUTOMATIC	APSTR214	0	0
218	AUTOMATIC	APSTR215	0	0
219	AUTOMATIC	APSTR216	0	0
220	AUTOMATIC	APSTR217	0	0
221	AUTOMATIC	APSTR218	0	0
222	AUTOMATIC	APSTR219	0	0
223	AUTOMATIC	APSTR220	0	0
224	AUTOMATIC	APSTR221	0	0
225	AUTOMATIC	APSTR222	0	0
226	AUTOMATIC	APSTR223	0	0
227	AUTOMATIC	APSTR224	0	0
228	AUTOMATIC	APSTR225	0	0
229	AUTOMATIC	APSTR226	0	0
230	AUTOMATIC	APSTR227	0	0
231	AUTOMATIC	APSTR228	0	0
232	AUTOMATIC	APSTR229	0	0
233	AUTOMATIC	APSTR230	0	0
234	AUTOMATIC	APSTR231	0	0
235	AUTOMATIC	APSTR232	0	0
236	AUTOMATIC	APSTR233	0	0
237	AUTOMATIC	APSTR234	0	0
238	AUTOMATIC	APSTR235	0	0
239	AUTOMATIC	APSTR236	0	0
240	AUTOMATIC	APSTR237	0	0
241	AUTOMATIC	APSTR238	0	0
242	AUTOMATIC	APSTR239	0	0
243	AUTOMATIC	APSTR240	0	0
244	AUTOMATIC	APSTR241	0	0
245	AUTOMATIC	APSTR242	0	0
246	AUTOMATIC	APSTR243	0	0
247	AUTOMATIC	APSTR244	0	0
248	AUTOMATIC	APSTR245	0	0
249	AUTOMATIC	APSTR246	0	0
250	AUTOMATIC	APSTR247	0	0
251	AUTOMATIC	APSTR248	0	0
252	AUTOMATIC	APSTR249	0	0
253	AUTOMATIC	APSTR250	0	0
254	AUTOMATIC	APSTR251	0	0
255	AUTOMATIC	APSTR252	0	0
256	AUTOMATIC	APSTR253	0	0
257	AUTOMATIC	APSTR254	0	0
258	AUTOMATIC	APSTR255	0	0
259	AUTOMATIC	APSTR256	0	0
260	AUTOMATIC	APSTR257	0	0
261	AUTOMATIC	APSTR258	0	0
262	AUTOMATIC	APSTR259	0	0
263	AUTOMATIC	APSTR260	0	0
264	AUTOMATIC	APSTR261	0	0
265	AUTOMATIC	APSTR262	0	0
266	AUTOMATIC	APSTR263	0	0
267	AUTOMATIC	APSTR264	0	0
268	AUTOMATIC	APSTR265	0	0
269	AUTOMATIC	APSTR266	0	0
270	AUTOMATIC	APSTR267	0	0
271	AUTOMATIC	APSTR268	0	0
272	AUTOMATIC	APSTR269	0	0
273	AUTOMATIC	APSTR270	0	0
274	AUTOMATIC	APSTR271	0	0
275	AUTOMATIC	APSTR272	0	0
276	AUTOMATIC	APSTR273	0	0
277	AUTOMATIC	APSTR274	0	0
278	AUTOMATIC	APSTR275	0	0
279	AUTOMATIC	APSTR276	0	0
280	AUTOMATIC	APSTR277	0	0
2				

- Option 2 (this will print in the log instead of the output window):

```
%put _automatic_;
```
 - Option 3:

```
Proc sql;
  Select *
    From dictionary.macros
  Where scope =
    "AUTOMATIC";
Quit;
```
- In options 1 and 3 above, "AUTOMATIC" may be replaced by "USER", "GLOBAL", or "LOCAL" to get customized lists. Note that since you are specifying the value of a variable, it is case-sensitive.
 - In option 2 above, _automatic_ may be replaced by _user_, _local_, _global_, or _user_.

%let Statement to Create a Macro Variable

We have already seen the %let statement used to create a macro variable. As stated, within a %let statement the name of the macro variable is to the left of the equal sign. Everything to the right of the equal sign up to but not including the semi-colon, except leading and trailing blanks, is the value of the macro variable.

The following example illustrates these concepts.

```
Command ===>
00001 %let mvar1=value;
00002 %let mvar2= value ;
00003 %let mvar3 = value;
00004 %let mvar4='value';
```

Line	Comment
00001	Macro variable definition does not include leading or trailing blanks.
00002	Macro variable definition contains leading and trailing blanks.
00003	Macro variable definition with leading blanks.
00004	Macro variable value enclosed in single quotes.

What do these macro variables resolve to?

Specifically, what about leading and trailing blanks?

Do quotation marks become part of the value?

We will use the %put statement to examine the values of these macros.

```
Command ===>
00001 %let mvar1=value;
00002 %put mvar1;
00003
00004 %let mvar2= value ;
00005 %put mvar2;
00006
00007 %let mvar3 = value;
00008 %put mvar3;
00009
00010 %let mvar4='value';
00011 %put mvar4;
00012
```

Inspect the results of these paired %let and %put statements in the log.

```
Line      Comment
12      %let mvar1=value;
13      %put mvar1;
14      value
15
16      %let mvar2= value ;
17      %put mvar2;
18      value
19
20      %let mvar3 = value;
21      %put mvar3;
22      value
23
24      %let mvar4='value';
25      %put mvar4;
26      'value'
```

Line	Comment
after 17	Resolution of &mvar1 to value
after 20	Resolution of &mvar2 to value (no leading or trailing blanks)
after 23	Resolution of &mvar3 (no leading blanks on the macro name)
after 26	Resolution of &mvar4 to 'value' (includes quotes)

In some cases, it is clear that the leading blanks were not included as part of the macro variable value. (In the Log, they are written flush with the left margin.)

However, how can we test for trailing blanks?

To do so, insert a character string around the macro variable as shown.

```
Command ===>
00001 %let mvar1=value;
00002 %put mvar1;
00003
00004 %let mvar2= value ;
00005 %put mvar2;
00006
00007 %let mvar3 = value;
00008 %put mvar3;
00009
00010 %let mvar4='value';
00011 %put mvar4;
00012
```

Inspect the Log again for the macro variable values.

```
Line      Comment
17      %let mvar1=value;
18      %put mvar1;
19      value
20
21      %let mvar2= value ;
22      %put mvar2;
23      value
24
25      %let mvar3 = value;
26      %put mvar3;
27      value
28
29      %let mvar4='value';
30      %put mvar4;
31      'value'
```

Null Values

One particular %let statement is used to assign a null value to the macro variable.

```
Command ===>
00001 %let mvar1=;
00002
00003 %put mvar1;
00004
```

Line	Comment
00001	%let statement creates a macro variable with null value. (This will be useful later for controlling which symbol table receives the macro value as well as eliminating unwanted macro variable values.)

```
Line      Comment
33      %let mvar1=;
34      %put mvar1;
35      
```

%let Statement – Another Look

Now inspect the following %let statements.

Both will result in the same value for the macro variables.

What is the value? Why?

```

Command ===>
00001 %let var5=proc print;
00002 %put &&var5;
00003
00004 %let var6=proc print; run;
00005 %put &&var6;
00006

```

```

Command ===>
00001 %let var5=proc print;
00002 %put &&var5;
00003
00004 %let var6=proc print; run;
00005 %put &&var6;
00006

```

Line	Comment
after 42	The %let statement stops at semi-colon. &var5 resolves to <i>proc print</i> .
after 45	The %let statement stops at first semi-colon. &var6 resolves to <i>proc print</i> .

The semi-colon has special meaning associated with it. When *var5* is defined, the %let statement ends at the semi-colon. The value of macro variable *var5* is *proc print*.

The same process is followed for *var6* where the first semi-colon ends the %let statement. The semi-colon is not treated as 'just another' keystroke; it has functionality.

There are times when we need characters to be 'just another' character without functionality.

%STR and %NRSTR Functions

Two functions – %str() and %nrstr() – provide a means to remove the special meaning of certain characters:

%str() – eliminates the functionality of most special characters, except for the ampersand and percent symbols. It does not remove the meaning of apostrophes.

%nrstr() – eliminates the functionality of most special characters, including the ampersand and percent symbols. It does not remove the meaning of apostrophes.

The following table illustrates the use of these two functions.

%let statement	Macro Variable Call	Macro Variable Value
%let Task1 = Proc print;	&Task1	Proc print
%let Task2=%str(Proc print);	&Task2	Proc print;
%let Task3=%str(Proc print; run);	&Task3	Proc print; run;
%let More=%str(&task1; run);	&More	Proc print; run;
%let More1=%nrstr(&task1;run;);	&More1	&task1; run;
Macro Call		Comment
&Task1		Note that the semi-colon is not part of the resolved macro value.
&Task2		Note the semi-colon in the resolved macro value
&More		The macro variable &task1 resolves in the %str() function.
&More1		The macro variable &task1 does not resolve in the %nrstr() function.

Using the %STR Function

As an example of using the %str function consider the following code. Proc Print is used to print the first ten observations from a data set and then Proc Contents is used to display the descriptor part of the data set.

```

Command ===>
00001 proc print data=saved.demog (obs=10) noobs;
00002 run;
00003
00004 proc contents data=saved.demog;
00005 run;
00006

```

Assume you wished to run this code multiple times. One approach would be to type this code whenever needed.

Another approach is to make this entire code a macro variable. To include the semi-colon as part of the macro value the %str function is used.

```

Command ===>
00001 %let debug = %str(
00002 proc print data=saved.demog (obs=10) noobs;
00003 run;
00004
00005 proc contents data=saved.demog;
00006 run;
00007 );

```

Now, anytime the programmer wishes to use this code, a shorter syntax can be used.

```

Command ===>
00001 %debug;
00002

```

Now consider a situation in which an apostrophe is part of a macro variable value. Neither the %str nor the %nrstr functions remove the functionality of the apostrophe. To remove this special meaning it is necessary to place a % sign in front of the apostrophe.

```

Command ===>
00001 %let name=%str( From America's Corp.);
00002
00003 title "&name";
00004 proc print data=saved.demogrf;
00005 run;
00006 title;

```

```

Command ===>
From America's Corp.

Obs   age   gender   salary   status   children
1      34      M      40000      M         4
2      34      M      23000      M         3
3      36      M      23000      M         2
4      40      M      12300      M         2
5      28      M      12000      M         2

```

Removing Macro Variables from the Global Symbol Table

Once a macro variable is created, that is written to the Global Symbol Table, it exists until it is explicitly deleted. Symbol tables will be discussed in greater detail in a subsequent chapter. For present considerations, it is necessary to know that a macro variable created by a %let statement in open code (outside a macro bundle) is written to the Global Symbol Table.

Symdel is used to delete macro variables. *Symdel* can be used either as a macro statement or as a call routine in a data step. The macro statement form is illustrated below.

```
Command ==>
00001 Xlet company = SAS Institute;
00002
00003 Xput company = &company;
00004
00005 Xsymdel company;
00006
00007 Xput company = &company;
00008
```

```
Command ==>
00001 Xlet company = SAS Institute;
00002
00003 Xput company = &company;
00004 company = SAS Institute;
00005
00006 Xsymdel company;
00007
00008 Xput company = &company;
00009
WARNING: Apparent symbolic reference COMPANY not resolved.
00010 company = &company;
00011
```

Line	Comment
00001	%let statement creates a macro variable.
00003	%put statement prints the label and variable in the log.
00005	%symdel statement deletes the macro variable from the global symbol table.
00007	%put statement attempts to print the variable after the deletion; the log shows that the variable no longer exists.

The call routine form of *Symdel* is illustrated below.

```
Command ==>
00001 Xlet company = SAS Institute;
00002
00003 Xput company = &company;
00004
00005 data _null_;
00006 call symdel("company");
00007 run;
00008
00009 Xput company = &company;
00010
```

```
Command ==>
00001 Xlet company = SAS Institute;
00002
00003 Xput company = &company;
00004 company = SAS Institute;
00005
00006 data _null_;
00007 call symdel("company");
00008 run;
00009
NOTE: DATA statement used:
      real time    0.00 seconds
      cpu time     0.00 seconds
00010
WARNING: Apparent symbolic reference COMPANY not resolved.
00011
00012 Xput company = &company;
00013
00014
```

Line	Comment
00001	%let statement creates a macro variable.
00003	%put statement prints the label and variable in the log.
00005 – 00007	The <i>symdel</i> call routine deletes the macro variable from the global symbol table. Notice the macro variable reference – no ampersand, but enclosed in quotes (either single or double quotes will work)
00009	%put statement attempts to print the variable after the deletion; the log shows that the variable no longer exists.

Resolution Considerations

Macro programming relies on invoking a macro value by naming and resolving the macro variable.

Various programming issues often require a macro variable to be embedded in another character string. In this chapter we examine how these macros are identified and processed.

Macro Variable as a Suffix

We have seen that an ampersand followed by a non-blank character is treated as a macro variable name and resolved.

How is a macro variable name identified and processed when it is part of another character string? As part of another character string a macro variable is resolved and the result is concatenated with the remaining character string. A blank, an ampersand (&) or a dot (.) indicate the end of a macro variable name.

Consider the following example:

```
Program Editor - n01.1
Command ==>
00001 Xlet ds=demograf;
00002 Xlet gend=M;
00003
00004 title "Output for Data Set &ds";
00005
00006 data work.only&gend;
00007   set saved.&ds;
00008   where gender="&gend";
00009 run;
00010 proc print data=work.only&gend;
00011 run;
```

Line	Comment
00006	Name of data set being created is work.onlyM.
00007	Data set being read is saved.demograf
00008	Where clause resolves to: where gender="M";

Consider a second example:

A SAS library contains data sets named after a state's two-letter abbreviation and the fiscal years from 1990 to 1999. Thus, AZ1990, AZ1991, ... AZ1999 are examples of the data set names.

You must change the date structure in each of the 10 data sets as well as manipulate each data set to produce statistics and graphic output.

How can macros provide quick access to making changes accommodating each of the ten data sets?

The solution is a simple application of the %let statement.

```
Program Editor - n01.2
Command ==>
00001 /* Fill in the year value below */
00002 Xlet year=1996;
00003
00004 /*****
00005  No changes required in program below this point
00006 *****/
00007
00008 data work.az&year;
00009   set archivas.az&year;
00010   date1=substr(data,1,5);
00011   date2=substr(data,8,2);
00012   date=trim(date1)||'is'||trim(date2);
00013   drop date1 date2;
00014 run;
00015
00016 proc means data=work.az&year;
00017 run;
00018
00019 ....
00020
```

Line	Comment
00001	Use comments to provide user assistance.
00002	The %let statement allows the year value to change throughout the program. In this case the value 1996 has been entered.
00004	Stop the user from making changes where unnecessary.

All changes are consolidated at the top of the program.

Rather than changing every reference to the data set all through the entire length of the program, we can reference the data set name through a macro variable and generate the correct name each time.

Macro Variable as a Prefix

In the next example an attempt is made to use a macro variable in front of other text.

```

Program Editor - m4.3
Command ==>
00001 %let lib=saved;
00002
00003 data work.junk1;
00004   set &lib.catch;
00005 run;
00006
00007 proc print data=work.junk1;
00008 run;

```

Line	Comment
00004	Resolves to saved.catch

As the log indicates this results in an error.

```

Log (Filtered)
Command ==>
31 %let lib=saved;
32
33 data work.junk1;
34   set &lib.catch;
ERROR: File WORK.SAVEDCATCH.DATA does not exist.
35 run;

```

As part of the process to identify the end of the macro name the dot (.) is absorbed. Therefore, when the macro resolves, the dot (.) is removed and not left behind as part of the remaining character string.

By adding a second dot (.) the macro resolves properly. The first dot (.) operates as discussed while the second dot (.) is simply part of the remaining character string.

```

Program Editor - m4.4
Command ==>
00001 %let lib=saved;
00002
00003 data work.junk1;
00004   set &lib..catch;
00005 run;
00006
00007 proc print data=work.junk1;
00008 run;

```

Line	Comment
00004	Resolves to saved.catch

As another example:

A SAS library contains data sets named after each state's two-letter abbreviation and the fiscal year 1999. Thus, AZ1999, CT1999, HI1999, NY1999 are examples of the data set names.

You must change the date structure in each of the 50 data sets as well as manipulate the data set to produce statistics and graphic output.

How can macros provide quick access making changes accommodating each of the fifty data sets?

At first, it would seem that the %let statement would work.

Note: This program demonstrates a programming error.

```

Program Editor - m4.5
Command ==>
00001 /* fill in the state value below */
00002 %let st=CT;
00003
00004 /*****
00005  No changes required in program below this point
00006  *****/
00007
00008 data work.&st1999;
00009   set work.&st1999;
00010   date1=substr(date,1,5);
00011   date2=substr(date,6,2);
00012   date=trim(date1)||'19'||trim(date2);
00013   drop date1 date2;
00014 run;
00015
00016 proc means data=work.&st1999;
00017 run;
00018

```

The program soon shows a problem. Rather than search for the macro variable st, SAS searches for the macro variable st1999.

The program must be revised to end the macro name explicitly with a dot (.).

```

Program Editor - m4.6
Command ==>
00001 /* fill in the state value below */
00002 %let st=CT;
00003
00004 /*****
00005  No changes required in program below this point
00006  *****/
00007
00008 data work.&st.1999;
00009   set work.&st.1999;
00010   date1=substr(date,1,5);
00011   date2=substr(date,6,2);
00012   date=trim(date1)||'19'||trim(date2);
00013   drop date1 date2;
00014 run;
00015
00016 proc means data=work.&st.1999;
00017 run;
00018

```

Line	Comment
00008, 00009, 00016	The macro variable call of &st. will resolve to the value desired.

Remember that SAS uses the dot for other syntax reasons such as:

Usage of Dot	Example
Multiple-level names	Source.data Source.project.data.entry
First-dot / Last-dot	If first.gender = 0 then;
Formats / Informats	Dollar12.2
Missing numerics	Where salary ne .;
Naming output	Put '';

Append Two Macro Variables Together

Often two or more macro variables are incorporated into a single character string. Again, the issue is how is the macro variable name identified and processed.

In the following example the macro variables dsn and n are used together to identify the data set to be printed. Which data set is printed?

```

Program Editor - m4.7
Command ==>
00001 %let dsn=contour;
00002
00003 %let n=2;
00004
00005 %let dsn2=oilwell12;
00006
00007 title "Data Set saved.&dsn&n";
00008 proc print data=saved.&dsn&n;
00009 run;
00010 title;
00011

```

The ampersand (&) indicates the beginning of a macro variable name. Therefore, &dsn is considered one macro variable name while &n refers to a second macro variable. The entire character string resolves to saved.contour2.

Line	Comment
00001, 00003, 00005	Create macro variables <i>dsn</i> , <i>n</i> , and <i>dsn2</i> .
00007, 00008	Resolves to saved.contour2

Output (limited)

Command ==>

Data Set saved.contour2				
Obs	DOSE	REGULARY	PULSE	SHAPE
1	40	4	115	BALLO
2	40	5	130	BALLO
3	40	6	130	BALLO
4	40	7	134	BALLO
5	40	8	140	BALLO

In the following example a dot (.) indicates the end of the first macro variable name (&dsn). The dot (.) acts as a delimiter and is removed as part of the process to identify the macro variable name. Because a second macro variable name follows, the dot (.) is not needed. This character string resolves to saved.contour2 just as in the previous example.

Program Editor - and_6

Command ==>

```

00001 %let dsn=contour;
00002
00003 %let n=2;
00004
00005 %let dsn2=oilwell2;
00006
00007 title "Data Set saved.&dsn.&n";
00008 proc print data=saved.&dsn.&n;
00009 run;
00010 title;

```

Line	Comment
00001, 00003, 00005	Create macro variables <i>dsn</i> , <i>n</i> , and <i>dsn2</i> .
00007, 00008	Resolves to saved.contour2

Output (limited)

Command ==>

Data Set saved.contour2				
Obs	DOSE	REGULARY	PULSE	SHAPE
1	40	4	115	BALLO
2	40	5	130	BALLO
3	40	6	130	BALLO
4	40	7	134	BALLO
5	40	8	140	BALLO

Finally, consider the following code. Which data set is printed?

Program Editor - and_9

Command ==>

```

00001 %let dsn=contour;
00002
00003 %let n=2;
00004
00005 %let dsn2=oilwell2;
00006
00007 title "Data Set saved.&dsn2";
00008 proc print data=saved.&dsn2;
00009 run;
00010 title;

```

Line	Comment
00001, 00003, 00005	Create macro variables <i>dsn</i> , <i>n</i> , and <i>dsn2</i> .
00007, 00008	Resolves to saved.oilwell2

Output (limited)

Command ==>

Data Set saved.oilwell2			
Obs	CONC	DISTANCE	ID
1	1000	0.1	A
2	1250	0.1	B
3	900	0.2	A
4	950	0.2	B
5	650	0.3	A

Macro Code Bundles

The regular job you submit to backup your data sets or produce your graphics can all be bundled up into a macro and then 'invoked' using one word – the name of the macro.

Program Editor - and_10

Command ==>

```

00001 %let startup =
00002 %let( libname archive "c:\asee";
00003
00004 proc copy in=archive out=work;
00005 select demograt demoglus / nontype=DATA;
00006 run;
00007
00008 libname archive clear;);
00009
00010 %startup;
00011

```

Line	Comment
00001-00008	The %let statement used with the %str function to write a short program.
00010	The macro startup is invoked with &startup; (i.e., ampersand, name, semi-colon).

The log shows the results.

Output (limited)

```

108 %let startup =
109 %let( libname archive "c:\asee";
110
111 proc copy in=archive out=work;
112 select demograt demoglus / nontype=DATA;
113 run;
114
115 libname archive clear;);
116
117 %startup;
NOTE: LIBNAME ARCHIVE refers to the same physical library as SAUED.
NOTE: LIBREF ARCHIVE was successfully assigned as follows:
Engine:
Physical Name: C:\asee
Copying ARCHIVE.DEMOGRAF to WORK.DEMOGRAF (nontype=DATA).
NOTE: There were 40 observations read from the dataset ARCHIVE.DEMOGRAF.
NOTE: The data set WORK.DEMOGRAF has 40 observations and 6 variables.
NOTE: Copying ARCHIVE.DEMOGIUS to WORK.DEMOGIUS (nontype=DATA).
NOTE: There were 104 observations read from the dataset ARCHIVE.DEMOGIUS.
NOTE: The data set WORK.DEMOGIUS has 104 observations and 18 variables.
NOTE: PROCEDURE COPY used:
real time 1.30 seconds

NOTE: LIBREF ARCHIVE has been deallocated.

```

Reusing fixed programs is one advantage of a macro. Rather than retype a lengthy set of programming instructions, it is easier to create a macro program and call it with a single word.

The limiting feature of the previous example is its inability to adapt to changing needs. Suppose the programmer needs a different data set copied.

As currently written it would be necessary to add the name of the new data set to the Proc Copy select statement. Greater flexibility can be achieved by incorporating a macro variable into the select statement.

```

Command sas
00001 %let more = computer;
00002 %let startup =
00003   %str(libname archive "a:\sas");
00004
00005   proc copy in=archive out=work;
00006     select demogref demoglus more / nontypedata;
00007   run;
00008
00009   libname archive clear;
00010
00011 %startup;
00012

```

Line	Comment
00006	The &more macro variable makes it possible to specify additional data sets.

Notice that in the above example a single additional data set has been copied.

To copy several additional data sets simply list the data sets as the value of the macro variable.

```

Command sas
00001 %let more = computer carhire opt;
00002 %let startup =
00003   %str(libname archive "a:\sas");
00004
00005   proc copy in=archive out=work;
00006     select demogref demoglus more / nontypedata;
00007   run;
00008
00009   libname archive clear;
00010
00011 %startup;
00012

```

Line	Comment
00006	The %let statement defines multiple data sets to copy along with the ones already identified.

%Macro - %Mend

SAS can define a series of programming statements in an alternate manner.

Rather than use the %let = %str() or %let = %nrstr() syntax, begin the code with %macro statement and end it with %mend statement.

The rewritten program is shown below.

```

Command sas
00001 %macro startup;
00002   libname archive "a:\sas";
00003
00004   proc copy in=archive out=work;
00005     select demogref demoglus / nontypedata;
00006   run;
00007
00008   libname archive clear;
00009 %mend startup;
00010
00011 %startup;
00012

```

Line	Comment
00001-00009	A macro bundle is created using %macro and %mend syntax.
00011	The macro bundle startup1 is invoked with %startup1 (i.e., percent and name only – no semi-colon).

Notice that the macro call, %startup1, does not include a semi-colon.

There is no need here as a semi-colon has been generated by the macro call.

The code within the definition is complete, so no extra semi-colon is required.

%Macro - %Mend Notes

- A macro bundle – defined by %macro - %mend statements – must be defined before the named bundle can be called.
- Macro definitions start with the %macro statement that defines the name of the macro.
- The definition continues until the %mend statement.
- Including the macro name in the %mend statement is optional but advised.
- The macro is called or invoked by typing the macro name (no semi-colon).

A macro may contain:

- Data and Proc step code
- Macro programming statements and functions

As a second example, consider the following code.

```

Command sas
00001 data work.batch;
00002   set sasdata.demoglus;
00003   if age > 25 then newsal = salary * 1.2;
00004   else newsal = salary * 1.1;
00005   keep age staffno salary newsal;
00006 run;
00007
00008 proc print data=work.batch;
00009   title "Pay Review on Bayedates";
00010 run;
00011

```

How can we bundle this code so all we have to type to execute the code is a single word?

Use the %macro - %mend syntax.

```

Command sas
00001 %macro money;
00002   data work.batch;
00003     set sasdata.demoglus;
00004     if age > 25 then newsal = salary * 1.2;
00005     else newsal = salary * 1.1;
00006     keep age staffno salary newsal;
00007   run;
00008
00009   proc print data=work.batch;
00010     title "Pay Review on Bayedates";
00011   run;
00012 %mend money;
00013
00014 %money;
00015

```

The macro name may be omitted in the %mend statement because the SAS System will default to ending the last macro.

However, the %mend statement is critical. The macro processor takes control when a %macro statement is seen. Should the %mend be missing, everything from the %macro statement is regarded as being part of the open macro definition.

There are occasions when all the submitted code appears to be written to the log and nothing else - the code appears to be disappearing into a black hole! On such occasions, check for the absence of a %mend statement.

Macro Bundle Parameters

In the %money example, the data set names were fixed. How can we write a macro invoking any name for the library and data sets involved?

The way to do this is to pass parameters to the macro bundle. To use this method, the macro must be defined as requiring parameters.

Macro bundle parameters are created by listing variables in a set of parentheses next to the name of the macro bundle. The parameters are nothing more than macro variables available for use within the macro bundle. Within the bundle the macro variables are referenced just as we have seen before, with an ampersand followed by the macro variable name. When the macro is called the values for the parameters are specified in a set of parentheses next to the name of the macro.

There are two types of macro bundle parameters, positional and keyword.

Positional Parameters

The following example shows the creation of a single positional parameter.

```
Command ***
00001 %macro money (lib);
00002 data work.batch;
00003 set &lib..demoglus;
00004 if age > 35 then newvar = salary * 1.2;
00005 else newvar = salary * 1.5;
00006 keep age staffno salary newvar;
00007 run;
00008
00009 proc print data=work.batch;
00010 title "Pay Review on &lib";
00011 run;
00012 %mend money;
00013
00014 %money (saved);
00015
```

Line	Comment
00001	The positional parameter <i>lib</i> is established.
00014	The value 'saved' replaces each macro call for &lib.

The above example is logically equivalent to:

```
%let lib = saved;
```

Multiple parameters may be created. Multiple positional parameters are simply listed with a comma between parameters. For positional parameters variable names and associated values are determined by the position or order of the parameters.

In the following example two positional parameters are created.

```
Command ***
00001 %macro money (lib, var);
00002 data work.batch;
00003 set &lib..demoglus;
00004 if age > 35 then &var = salary * 1.2;
00005 else &var = salary * 1.5;
00006 keep age staffno salary &var;
00007 run;
00008
00009 proc print data=work.batch;
00010 title "Pay Review on &lib";
00011 run;
00012 %mend money;
00013
00014 %money (saved, outgo);
00015
```

Line	Comment
00001	Two positional parameters are established, <i>lib</i> and <i>var</i> respectively.
00014	The value 'saved' is substituted for the first positional parameter – <i>lib</i> – and the value 'outgo' is substituted for the second positional parameter – <i>var</i> .

Your macro call must have a number of values matching the number of positional parameters.

Keyword Parameters

Keyword parameters are defined using the parameter name with an equal sign. This technique is preferred in certain situations because:

- It does not require defining and passing parameters in the same order.
- It allows default values to be used.

Two keyword parameters are created in the following example.

```
Command ***
00001 %macro money (lib=, var=);
00002 data work.batch;
00003 set &lib..demoglus;
00004 if age > 35 then &var = salary * 1.2;
00005 else &var = salary * 1.5;
00006 keep age staffno salary &var;
00007 run;
00008
00009 proc print data=work.batch;
00010 title "Pay Review on &lib";
00011 run;
00012 %mend money;
00013
00014 %money (lib=saved, var=outgo);
00015
```

Line	Comment
00001	Two keyword parameters are created – <i>lib</i> and <i>var</i> .
00014	The values are assigned for the keyword parameters. The order of assigning values is not important with keyword parameters.

In the next example default values are assigned to the macro parameters.

```
Command ***
00001 %macro money (lib=saved, var=newvar);
00002 data work.batch;
00003 set &lib..demoglus;
00004 if age > 35 then &var = salary * 1.2;
00005 else &var = salary * 1.5;
00006 keep age staffno salary &var;
00007 run;
00008
00009 proc print data=work.batch;
00010 title "Pay Review on &lib";
00011 run;
00012 %mend money;
00013
00014 %money ();
00015
```

Line	Comment
00001	Two keyword parameters are created, with default values assigned.
00014	The macro invocation uses the default parameters.

Parentheses must be used when invoking a macro with keyword parameters. If no values are being passed an empty set of parentheses is used.

Null Values

With positional parameters null values are assigned by using a comma as a 'placeholder':

```
Command ***
00001 %macro printme (de, opt, feature);
00002 proc print data=saved.kde koptes;
00003 &feature;
00004 run;
00005 %mend printme;
00006
00007 %printme (demoglus, d noobe uniform, where gender = "F");
00008 %printme (demoglus, format salary dollar12.2);
00009 %printme (demoglus, );
00010
```



```

Command ===>
00001 %macro age(new, old, old_0, old_1, old_2, library=saved);
00002   proc datasets data=&library;
00003     age &new &old_0 &old_1 &old_2;
00004   run;
00005 %mend age;
00006

```

Define the macro in the normal way except for the / PARMBUFF option.

```

Command ===>
00001 %macro age / parmbuff;
00002   proc datasets data=&library;
00003     age &new &old_0 &old_1 &old_2;
00004   run;
00005 %mend age;
00006

```

Here, all supplied parameters, including any special characters used, are assigned to the automatic local macro variable &Syspbuff which is then manipulated in the macro by macro programming statements.

The call displayed in the code displayed below gives a value to &syspbuff of *library=mylib,new,old_0,old_1,old_2*.

```

Command ===>
00001 %age(new,old_0,old_1,old_2, library=mylib);
00002

```

Parameters may also be included in the definition

```

Command ===>
00001 %macro age(posparm) / parmbuff;
00002   %do i=1 %syspbuff;
00003     macro programming statements
00004   %end;
00005 %mend age;
00006

```

In the above example, a different number of parameters can be supplied as long as there is at least one.

```

Command ===>
00001 %age(new,old_0,old_1,old_2,mylib);
00002

```

The call gives a value to &syspbuff of *mylib,new,old_0,old_1,old_2* and &posparm the value *mylib*.

```

Command ===>
00001 %macro t / parmbuff;
00002   data _null_;
00003     j = "&syspbuff";
00004     v = scan(j, 1, '{');
00005     call symput('t', v);
00006   run;
00007   proc print data=saved.demog1.us;
00008     var ag;
00009   run;
00010 %mend t;
00011 %t (age salary weight cars)
00012

```

Here the value (age salary weight cars) has been passed to &syspbuff.

The _null_ data step is required to remove the parentheses from around the variable names.

&Syspbuff is found in a symbol table local to the executing macro.