

Macros - Intermediate

Prepared by



Global Business Intelligence
Consulting and Training

Destiny Corporation
100 Great Meadow Rd Suite 601
Wethersfield, CT 06109-2379

Phone: (860) 721-1684 1-800-7TRAINING Fax: (860)

721-9784

Email: info@destinycorp.com

Web: www.destinycorp.com

Overview

All the macro variables we have seen so far have been referenced using a single ampersand. This is known as direct referencing. These macros have resolved at 'the first attempt' or have not resolved at all.

```
Program Editor - m5.1
Command ==>
00001 %let mvar = test1;
00002 %put &mvar;
00003
```

Line	Comment
00001	The %let statement creates the macro variable <i>mvar</i> with value <i>test1</i> .
00002	The %put statement calls the macro variable <i>mvar</i> using a single ampersand. The resolved value is written to the Log.

However, various programming issues often require macro variables to be referenced using multiple ampersands. This is known as indirect referencing. This chapter examines how these macros are identified and processed.

Multiple Ampersands and Staggered Resolution

Consider the following code. What will &&dsn&n resolve to?

```
Program Editor - m5.2
Command ==>
00001 %let dsn=clinics;
00002 %let clinics5=How did I get here;
00003 %let n=5;
00004 %let dsn5=surprise;
00005
00006 %put &&dsn&n;
00007
```

Multiple ampersands are resolved using the following strategy:

- Start at the left-hand side and group ampersands into two's.
- Each set of double ampersands (&&) is resolved to a single ampersand (& => &)
- Each & followed by a character string is resolved as a macro variable
- A freestanding string remains unchanged.

- Repeat the above steps until all ampersands have been removed.

The above code is processed as follows:

Line	Comment
00001-00004	%let statements create macro variables.
00006	Call on &&dsn&n for staggered resolution:
	First pass: receives &&dsn&n
	resolves to: && => & dsn => dsn &n => 5
	Second pass: receives &dsn5
	resolves to: surprise

```
Log - (Untitled)
Command ==>
1 %let dsn=clinics;
2 %let clinics5=How did I get here;
3 %let n=5;
4 %let dsn5=surprise;
5
6 %put &&dsn&n;
surprise
```

Now, how will &&&dsn&n resolve?

```
Program Editor - m5.3
Command ==>
00001 %let dsn=clinics;
00002 %let clinics5=How did I get here;
00003 %let n=5;
00004 %let dsn5=surprise;
00005
00006 %put &&&dsn&n;
00007
```

00001-00004	%let statements create macro variables.
00006	Call on &&&dsn&n for staggered resolution:
	First pass: receives &&&dsn&n
	resolves to: && => & dsn => clinics &n => 5
	Second pass: receives &clinics5
	resolves to: How did I get here

```
Log - (Untitled)
Command ==>
7 %let dsn=clinics;
8 %let clinics5=How did I get here;
9 %let n=5;
10 %let dsn5=surprise;
11
12 %put &&&dsn&n;
How did I get here
```

Examples of the form (&&&*mvar*) are rare whereas the generation of multiple macro variables using &&root&suffix to give &root1, etc. are quite common. Any number of ampersands can be used.

As a final example, changing the value of *i* causes different macro variables to be referenced. This is used to print different titles.

```

Program Editor - m5.4
Command ==>
00001 %let title1=First Title for Saved.demograf;
00002 %let title2=Second Title for Saved.demograf;
00003 %let title3=Yet Another Title for Saved.demograf;
00004
00005 %let i=1;
00006
00007 title "&title&i!";
00008 proc tabulate data=saved.demograf;
00009   class status gender;
00010   var salary;
00011   table status, gender*salary;
00012 run;

```

Output (Bundled)

Command ==>

First Title for Saved.demograf

	gender	
	F	M
	salary	salary
	Sum	Sum
status		
D	8000.00	20000.00
H	131600.00	110300.00
S	43000.00	17000.00
SEP	18000.00	12000.00
U	30000.00	

Symbol Tables

This module examines the concept of symbol tables in greater depth. It has already been pointed out that macros live in symbol tables. It is critical to know which symbol table receives a macro.

Correct use of macro values requires the programmer to know how to change or avoid changing macro variable values in specific symbol tables.

This module develops the default rules for placing macro variables into global and local symbol tables. However, sometimes the default rules are not what the programmer needs. After examining default placement rules, this module looks at how to assure that macro variables are written to the symbol table of the programmer's choice.

Symbol Table Rules

At SAS invocation time, the Automatic Symbol Table (AST) is built containing most of the automatic macro variables.

An executing macro builds a symbol table local to it. This symbol table is deleted once the macro has ceased execution.

Just like the Data Step, the macro first compiles (when defined) and then executes (when called).

The `%macro` statement signals the start of the macro definition.

The macro processor takes all the code that follows until it reaches the `%mend` statement, compiling the code and saving it in the Work library.

The default location for a `%macro` - `%mend` bundle is the `Sasmacr` catalog in the Work library.

The 'compiled' form is a mixture of compiled statements and constant text.

Upon a macro call, the macro processor retrieves the compiled macro code from the Work library and executes it, placing any generated code upon the SAS input stack as text. During macro execution, the macro processor may pause while text placed upon the input stack is processed. That is to say, once a full step is placed upon the input stack, there will be a pause while it is executed.

However, macro execution does one further thing. It creates a symbol table local to the executing macro for the duration of the execution of that macro. Once the execution of the macro has completed, the local symbol table is deleted.

In addition, we now know another way of defining macro variables – as parameters (either positional or keyword) in the definition of a macro. The macro variables defined in this way are always and only placed in the symbol table local to the macro. So, during the macro execution, there is access to two symbol tables - the local one and the global one. The local table is always searched before the global one. We shall return to this subject in the next module.

In this section, we illustrate the rules for the following:

- Writing to the various symbol tables during the execution of a macro
- Reading from the symbol tables.

There are several factors to keep in mind when working through the following examples. These include the following:

How is the macro variable defined?

1. `%let` statement,
2. parameter,
3. otherwise....

Where is the macro variable defined?

1. In open code
2. Within a macro bundle

What is the name of the macro variable?

1. Same as an already-existing macro variable
2. A totally new name

Example 1

```

Program Editor - m9.1
Command ==>
00003 %macro fiscal;
00004   %let quarter=1;
00005   %put ***&quarter***;
00006 %mend fiscal;
00007
00008
00009 %fiscal
00010
00011 %put ***&quarter***;
00012

```

Line	Comment
00004	The <code>%let</code> statement defines a macro inside a macro bundle.
00005	The <code>%put</code> statement tests the value of <code>&quarter</code> inside the macro bundle.
00011	The <code>%put</code> statements tests the value of <code>&quarter</code> after the macro bundle has finished executing.

The log is displayed below.

```

Log (Untitled)
Command ===>
55 %macro fiscal;
56   %let quarter=1;
57   %put &&&quarter&&&;
58 %mend fiscal;
59
60
61 %fiscal
62 *****
63 %put &&&quarter&&&;
WARNING: Apparent symbolic reference QUARTER not resolved.
&&&quarter&&&

```

Explanation

When `%fiscal` executes a symbol table local to the macro `fiscal` is established. With the local symbol table in place, the `%let` statement does the following:

Checks the most local table for the existence of a macro variable called `quarter`.

If a macro variable called `quarter` is found, its value is overwritten in that symbol table.

If a macro variable called `quarter` is not found, the macro processor checks the next higher table (i.e., here, the global symbol table) for the existence of a macro variable called `quarter`.

If a macro variable called `quarter` is found in the next higher table, its value is overwritten in that table.

If a macro variable called `quarter` is not found, the process of checking the next higher symbol table continues. If a macro variable called `quarter` is never found, a macro variable is created and its value assigned in the most local table (i.e., the first table searched).

So, in this example the macro called `quarter` is established in the table local to `fiscal`.

The `%put` statements now read from the tables. During the execution of `%fiscal`, the macro processor will do the following:

- Search the local table for the presence of `&quarter`, find it and report on the value. The `%put` statement inside the macro `fiscal` will therefore write the value of `quarter` to the log.
- When `%fiscal` completes the local symbol table is deleted. Therefore `quarter` no longer exists. An error occurs when the `%put` statement outside the macro `fiscal` attempts to write a nonexistent macro.

Before Execution	During Execution	After Execution
Global Symbol Table	Global Symbol Table	Global Symbol Table
	Local Symbol Table FISCAL	
	Quarter = 1	

Example 2

```

Program Editor - m9 2
Command ===>
00001 %let month=January;
00002
00003 %macro fiscal;
00004   %let quarter=1;
00005   %put &&&quarter&&&;
00006   %put &&&month&&&;
00007 %mend fiscal;
00008
00009
00010 %fiscal
00011 *****
00012 %put &&&quarter&&&;
00013 %put &&&month&&&;

```

Line	Comment
00001	The <code>%let</code> statement defines a macro in open code.
00004	The <code>%let</code> statement defines a macro inside a macro bundle.
00005, 00006	Two <code>%put</code> statements test the value of <code>&quarter</code> and <code>&month</code> inside the macro bundle.
00012, 00013	Two <code>%put</code> statements test the value of <code>&quarter</code> and <code>&month</code> after the macro bundle has finished executing.

```

Log (Untitled)
Command ===>
55 %fiscal
56 *****
57 %let month=January;
58 %put &&&quarter&&&;
WARNING: Apparent symbolic reference QUARTER not resolved.
&&&quarter&&&
59 %put &&&month&&&;
&&&month&&&

```

Explanation

When the first `%let` statement executes in open code it writes to the global symbol table. Therefore, the macro variable `month` is defined in the global symbol table with a value of January.

When `%fiscal` executes another scope is established, which is the symbol table local to the macro `fiscal`. With the local symbol table in place, the second `%let` statement operates as described previously.

In this example then, the macro variable `month` is established in the global symbol table whereas `quarter` is established in the table local to `fiscal`.

The `%put` statements now read from the tables. During the execution of `%fiscal`, the macro processor will do the following:

- Search the local table for the presence of `&month`.
- Upon failing to find it, macro processor will now search the global table, find it, and report the value.
- Search the local table for the presence of `&quarter`, find it and report on the value.
- When `%fiscal` completes, the local symbol table is deleted, so that the final `%put` statements have only the global table left to search. So, `&month` is found but `&quarter` is not.

Before Execution	During Execution	After Execution
Global Symbol Table	Global Symbol Table	Global Symbol Table
Month = January	Month = January	Month = January
	Local Symbol Table FISCAL	
	Quarter = 1	

Example 3

```

Program Editor m9.3
Command ===>
00001 %let month=January;
00002
00003 %macro fiscal;
00004     %let month=1;
00005     %put ***&month***;
00006 %mend fiscal;
00007
00008
00009 %fiscal
00010
00011 %put ***&month***;
00012

```

Line	Comment
00001	The %let statement defines a macro in open code.
00004	The %let statement defines a macro <u>with the same name</u> inside a macro bundle.
00005	The %put statement tests the value of &month <u>inside the macro bundle</u> .
00011	The %put statement tests the value of &month <u>after the macro bundle has finished executing</u> .

```

Log (Untitled)
Command ===>
***1***
108
109 %put ***&month***;
***1***

```

Explanation

The sequence of logic is the same here as for the previous example:

Macro variable *month* with value *January* is written to the global table.

Upon macro execution, the processor checks the most local environment for a macro variable called *month*. Failing to find it, it checks the next higher table(s). Upon finding a macro variable *month* in the global symbol table, the old value (*January*) is overwritten with the new value of *1*.

Both %put statements report from the global table, the 'inner' one checking the local table first.

Before Execution	During Execution	After Execution
Global Symbol Table	Global Symbol Table	Global Symbol Table
Month = January	Month = 1	Month = 1
	Local Symbol Table FISCAL	

Example 4

```

Program Editor m9.4
Command ===>
00001 %macro stats(region=);
00002     %put ***&region***;
00003 %mend stats;
00004
00005 %stats(region=CT)
00006
00007 %put &region;
00008

```

Line	Comment
00001	The keyword parameter defines a macro associated with the macro bundle.
00002	The %put statement tests the value of ®ion <u>inside the macro bundle</u> .
00007	The %put statements tests the value of ®ion <u>after the macro bundle has finished executing</u> .

```

Log (Untitled)
Command ===>
117 %macro stats(region=);
118     %put ***&region***;
119 %mend stats;
120
121 %stats(region=CT)
122 ***CT***
123 %put &region;
WARNING: Apparent symbolic reference REGION not resolved.
&region

```

Explanation

Macro variables created as parameters are placed only and always in the table most local to the macro (except for read-write automatic macros, see example 7).

Before Execution	During Execution	After Execution
Global Symbol Table	Global Symbol Table	Global Symbol Table
	Local Symbol Table STATS	
	Region = CT	

Example 5

```

Program Editor m9.5
Command ===>
00001 %let region=CT;
00002
00003 %macro stats(region=);
00004     %put ***&region***;
00005 %mend stats;
00006
00007 %stats(region=AZ)
00008
00009 %put ***&region***;
00010

```

Line	Comment
00001	The %let statement defines a macro in open code.
00003	The keyword parameter defines a macro of <u>the same name</u> associated with the macro bundle.
00004	The %put statement tests the value of ®ion <u>inside the macro bundle</u> .
00009	The %put statement tests the value of ®ion <u>after the macro bundle has finished executing</u> .

```

Log (Untitled)
Command ===>
130 %stats(region=AZ)
***AZ***
131
132 %put ***&region***;
***CT***

```

Explanation

Although the %let statement has already established the macro variable *region* in the global environment, the value is not overwritten by the parameter. Macro variables created as parameters are placed only and always in the table most local to the macro (except for read-write automatic macros, see example 7).

This example also illustrates the read sequence: the most local symbol table is always read first with the global and automatic tables last.

Before Execution	During Execution	After Execution
Global Symbol Table	Global Symbol Table	Global Symbol Table
Region = CT	Region = CT	Region = CT
	Local Symbol Table STATS	
	Region = AZ	

Example 6

```

Program Editor - m7_6
Command ==>
00001 %let sysdate9=15apr2003;
00002
00003 %macro test6;
00004     %let sysdate9=01jan2003;
00005
00006     %put &sysdate9;
00007
00008 %mend test6;
00009
00010 %test6
00011
00012 %put &sysdate9;

```

Line	Comment
00001	The %let statement attempts to define a macro variable using the name of a read-only automatic macro.

```

Log (Untitled)
Command ==>
ERROR: Attempt to assign a value to a read-only symbolic variable
(SYSDATE9).
26 %let sysdate9=15apr2003;
27
28 %macro test6;
29     %let sysdate9=01jan2003;
30
31     %put &sysdate9;
32
33 %mend test6;
34
35 %test6
ERROR: Attempt to assign a value to a read-only symbolic variable
(SYSDATE9).
04MAR2003
36
37 %put &sysdate9;
04MAR2003

```

Explanation

&sysdate9 is set by the system and is read only. The %let statement follows the standard write logic and the error message is given.

NOTE: Do not give your variables the same name as read-only automatic variables!

Before Execution	During Execution	After Execution
Automatic Symbol Table	Automatic Symbol Table	Automatic Symbol Table
Sysdate9 = 04MAR2003	Sysdate9 = 04MAR2003	Sysdate9 = 04MAR2003
Global Symbol Table	Global Symbol Table	Global Symbol Table

Example 7

```

Program Editor - m9_7
Command ==>
00001 %put &syslast;
00002
00003 %macro test7(syslast=);
00004     %put &syslast;
00005 %mend test7;
00006
00007 %test7(syslast=whatever)
00008
00009 %put &syslast;
00010

```

Line	Comment
00001	The %put statement tests the value of &syslast, a read-write automatic macro variable, before the bundle executes.
00003	The keyword parameter defines a macro with the same name as the automatic macro.
00004	The %put statement tests the value of &syslast inside the macro bundle.
00009	The %put statement tests the value of &syslast after the macro bundle has finished executing.

```

Log (Untitled)
Command ==>
213 %put &syslast;
WORK.DEMOGRAF
214
215 %macro test7(syslast=);
216     %put &syslast;
217 %mend test7;
218
219 %test7(syslast=whatever)
WORK.whatever
220
221 %put &syslast;
WORK.whatever

```

Explanation

&syslast is set by the system but is a read-write macro variable. The parameter to the bundle has the same name. The read sequence is the same as that discussed: the most local table is read first with the global and automatic tables read last. The difference in this example is that the value of the automatic variable is overwritten.

Before Execution	During Execution	After Execution
Automatic Symbol Table	Automatic Symbol Table	Automatic Symbol Table
Syslast = work.demograf	Syslast = work.whatever	Syslast = work.whatever
Global Symbol Table	Global Symbol Table	Global Symbol Table

Nested Macros

A nested macro refers to a macro invoked within another macro. Nested macros allow increased flexibility and control over program flow.

There are two basic structures for creating nested macros. In the first technique, one macro is completely defined within a second macro.

```

Program Editor m10.1
Command ==>
00001 %macro both(ds,by,out);
00002
00003 %macro sortit(dset,by1,out);
00004   proc sort data=saved.&dset out=work.&out;
00005     by &by1;
00006   run;
00007 %mend sortit;
00008
00009 %sortit(&ds,&by,&out)
00010
00011
00012 %macro printit(dset,by);
00013   title "Header Information for Data Set Work.&out";
00014   proc contents data=work.&out;
00015   run;
00016   title "Data Set Work.&out Sorted By &by";
00017   proc print data=work.&out;
00018   run;
00019   title;
00020 %mend printit;
00021
00022 %printit(&ds,&by)
00023
00024
00025 %mend both;
00026
00027 %both(demograf,gender,demograf)

```

Such a structure will work, but is inefficient. The inner macros are stored as text instead of being compiled. Each time the outer macro executes the inner macros are compiled.

A more efficient technique is to define each macro separately and then invoke the compiled macros:

```

Program Editor m10.2
Command ==>
00001 %macro sortit(dset,by1,out);
00002   proc sort data=saved.&dset out=work.&out;
00003     by &by1;
00004   run;
00005 %mend sortit;
00006
00007 %macro printit(dset,by);
00008   title "Header Information for Data Set Work.&out";
00009   proc contents data=work.&out;
00010   run;
00011   title "Data Set Work.&out Sorted By &by";
00012   proc print data=work.&out;
00013   run;
00014   title;
00015 %mend printit;
00016
00017 %macro both(ds,by,out);
00018   %sortit(&ds,&by,&out)
00019   %printit(&ds,&by)
00020 %mend both;
00021
00022 %both(demograf,gender,demograf)

```

Because all the macros are defined separately, they all compile. Here are the referencing environments:

When the outer macro, *both*, is executing, the referencing environment is:

- The symbol table local to *both* plus the global table.

When the middle macro, *sortit*, is executing, the referencing environment is:

- The symbol table local to *sortit*, the symbol table local to *both*, plus the global table.

When the inner macro, *printit*, is executing, the referencing environment is:

- The symbol table local to *printit*, the symbol table local to *sortit*, the symbol table local to *both*, plus the global table.

Note that as a macro's execution terminates, the symbol tables are deleted and the referencing environment is reduced again.

Controlling the Placement of Macro Variables

So far, we have seen default rules for placement of macro variables into symbol tables. These rules help the programmer determine the value passed to the program. Often the default rules permit efficient coding possibilities.

In contrast, there are times when the default rules for placement will work against the goals of the programmer.

A macro variable might go global and replace a value needed for reference in later portions of the program.

Conversely, the programmer might wish to confine a macro variable to a local symbol table. This strategy would help minimize the size of the global table over the course of the SAS session. Local tables are destroyed after the macro finishes executing.

Restricting as many macro variables to the local tables as possible helps increase efficiency in the SAS session.

This section examines situations where the default rules for placement of macro variables are at odds with programming goals.

The programmer seeks to keep a macro variable in the local table where otherwise it would go to the global table. The reverse case can also be true: the macro variable should be written to the global table but would be written locally by default.

Directing a Macro Variable to the Global Table

Sometimes a variable will be made local when the programmer seeks to place it in the GST. To allow its value to be used in another step, consider the following code:

```

Program Editor m10.3
Command ==>
00001 %macro subtest;
00002   %let status=N;
00003   data &status;
00004     set saved.demograf (where=(status="&status"));
00005   run;
00006 %mend subtest;
00007
00008 %macro printit;
00009   title "Subset of Demograf where Status = &status..";
00010   proc print data=&status (where=(status="&status"));
00011   run;
00012 %mend printit;
00013
00014 %subtest
00015 %printit
00016
00017

```

Line	Comment
00002	By default, the <code>%let</code> statement assigns the macro variable <code>status</code> to the most local table. The macro variable is unavailable during the execution of <code>%printit</code> .

The Log window shows the reason the program fails to print and create the correct title.

```

Log
NOTE: There were 82 observations read from the dataset SAVED.DEMOGRAF.
WHERE status='N'
NOTE: The data set WORK.N has 82 observations and 18 variables.
NOTE: DATA statement used:
real time 1.43 seconds

WARNING: Apparent symbolic reference STATUS not resolved.
NOTE: Line generated by the invoked macro "PRINTIT".
proc print data=&status
121
131 (where=(status="&status")); run;
WARNING: Apparent symbolic reference STATUS not resolved.
WARNING: Apparent symbolic reference STATUS not resolved.
ERROR 22-322: Expecting a name.
ERROR 18-222: Syntax error, statement will be ignored.
NOTE: The SAS System stopped processing this step because of errors.
NOTE: PROCEDURE PRINT used:
real time 0.48 seconds

```

How might this programming objective be realized?

```

Command 223
00001 %global status;
00002
00003 %macro subset;
00004 %let status=M;
00005 data _temp1;
00006 set saved.demogius (where=(status="F"));
00007 run;
00008 %mend subset;
00009
00010 %macro printit;
00011 title "Subset of Demogius where Status = &status.";
00012
00013 proc print data=_temp1 (where=(status="&status"));
00014 run;
00015 %mend printit;
00016
00017 %subsume;
00018 %printit;
00019
00020 %let status=F;
00021
00022 title;
00023

```

Line	Comment
00001	The %global statement directs the creation of a macro variable (in this case <i>status</i>) in the global table. The value of the variable is null.
00004	The %let statement inside %subset follows the default rules. The GST receives the value for <i>status</i> , just as the programmer had intended.

Directing a Macro Variable to the Local Table

The programmer may also want a macro variable to be written to the local symbol table.

This step would assure that a value in the global symbol table would not be overwritten.

Also, the global table would not become cluttered with macro variables used on a one-time basis.

```

Command 223
00001 %let gender=F;
00002 %put &&gender;
00003
00004 %macro genderM;
00005 %put &&gender;
00006 %let gender=M;
00007 proc means data=saved.demogius mean;
00008 var salary;
00009 where gender = "&gender";
00010 %put &&gender;
00011 run;
00012 %mend genderM;
00013
00014 %put &&gender;
00015
00016 %macro genderF;
00017 %put &&gender;
00018 proc means data=saved.demogius mean;
00019 var salary;
00020 where gender = "&gender";
00021 %put &&gender;
00022 run;
00023 %mend genderF;
00024
00025 %put &&gender;
00026
00027 %genderM
00028 %put &&gender;
00029
00030 %genderF
00031 %put &&gender;
00032

```

Line	Comment
00001	The %let statement in open code creates the macro variable <i>gender</i> in the GST with value <i>F</i> .
00006	The %let statement replaces the GST value of <i>gender</i> with <i>M</i> . This value is what the programmer wanted for the %genderM macro bundle.
00020	The &gender resolves to <i>M</i> , not <i>F</i> as the programmer had wanted.

```

00001 %let gender=F;
00002 %put &&gender;
00003
00004 %macro genderM;
00005 %put &&gender;
00006 %let gender=M;
00007 proc means data=saved.demogius mean;
00008 var salary;
00009 where gender = "&gender";
00010 %put &&gender;
00011 run;
00012 %mend genderM;
00013
00014 %put &&gender;
00015
00016 %macro genderF;
00017 %put &&gender;
00018 proc means data=saved.demogius mean;
00019 var salary;
00020 where gender = "&gender";
00021 %put &&gender;
00022 run;
00023 %mend genderF;
00024
00025 %put &&gender;
00026
00027 %genderM
00028 %put &&gender;
00029
00030 %genderF
00031 %put &&gender;
00032

```

```

NOTE: There were 84 observations read from the dataset SAVED.DEMOGIUS.
NOTE: PROCEDURE MEANS used:
      real time      1.88 seconds

00001 %let gender=F;
00002 %put &&gender;
00003
00004 %macro genderM;
00005 %put &&gender;
00006 %let gender=M;
00007 proc means data=saved.demogius mean;
00008 var salary;
00009 where gender = "&gender";
00010 %put &&gender;
00011 run;
00012 %mend genderM;
00013
00014 %put &&gender;
00015
00016 %macro genderF;
00017 %put &&gender;
00018 proc means data=saved.demogius mean;
00019 var salary;
00020 where gender = "&gender";
00021 %put &&gender;
00022 run;
00023 %mend genderF;
00024
00025 %put &&gender;
00026
00027 %genderM
00028 %put &&gender;
00029
00030 %genderF
00031 %put &&gender;
00032

```

The default rules have worked against the goals of the program.

The global macro variable *gender* was given a new value. To assure that the value of a macro variable is written to the local table, include syntax as shown.

```

Command 223
00001 %let gender=F;
00002 %put &&gender;
00003
00004 %macro genderM;
00005 %put &&gender;
00006 %local gender;
00007 %let gender=M;
00008 proc means data=saved.demogius mean;
00009 var salary;
00010 where gender = "&gender";
00011 %put &&gender;
00012 run;
00013 %mend genderM;
00014
00015 %put &&gender;
00016
00017 %macro genderF;
00018 %put &&gender;
00019 proc means data=saved.demogius mean;
00020 var salary;
00021 where gender = "&gender";
00022 %put &&gender;
00023 run;
00024 %mend genderF;
00025
00026 %put &&gender;
00027
00028 %genderM
00029 %put &&gender;
00030
00031 %genderF
00032 %put &&gender;
00033

```

Line	Comment
00006	The %local statement creates a macro variable <i>gender</i> in the symbol table local to %genderM. The value of <i>gender</i> is null.
00007	The default placement rules write the value to the local symbol table. The macro variable <i>gender</i> in the GST remains <i>F</i> .

Overview

This module looks at how the Data Step can create macro variables, often out of a data set variable. The *Call Symput* routine is used to create a macro variable from within the data step.

In addition, this module looks at the *Symget* function for bringing a macro variable into the Data Step.

Call Symput Routine

Of all the macro syntax options, Call Symput is one of the most important and most useful. With Call Symput, we have another way of creating a macro variable and giving it a value, this time during data step execution.

The syntax for call symput is:

Call symput (macro variable name, macro value);

Note:

- Call Symput is used exclusively in the Data Step.
- Call symput works at data step execution time (not compile time).
- The macro variable is not available until the data step creating it completes execution (i.e., until after the *run* statement).

Another issue to be aware is if the arguments are in quotes or not. Briefly, any argument enclosed in quotes is taken as the literal name or value. Any argument not in quotes is treated as a variable and the argument is the value of that variable.

Several examples follow illustrating this last point.

Example 1

```

Command Editor
00001 data _null_;
00002 call symput('newmacro', 'hello');
00003 run;
00004
00005 %put &&newmacro;
00006

```

Line	Comment
00002	Both arguments are in quotes. Argument one creates a macro variable <i>newmacro</i> with the value <i>hello</i> .

Example 2

```

Command Editor
00001 data _null_;
00002 x = 'mvar';
00003 call symput(x, 'greetings');
00004 run;
00005
00006 %put &&greetings;
00007

```

Line	Comment
00003	First argument unquoted and second argument quoted. Argument one references the data set variable 'x', which has the value of 'mvar'. Argument one creates a macro variable <i>mvar</i> with the value <i>greetings</i> .

Example 3

```

Command Editor
00001 data _null_;
00002 x = 'mvar';
00003 y = 'Monday';
00004 call symput(x,y);
00005 run;
00006
00007 %put &&greetings;
00008

```

Line	Comment
00004	Neither argument is in quotes. Arguments one and two reference data set variables 'x' and 'y' respectively. Both data set variables have values. Argument one creates a macro variable <i>mvar</i> with the value <i>Monday</i> .

Example 4

```

Command Editor
00001 data _null_;
00002 y = 'Monday';
00003 call symput('x',y);
00004 run;
00005
00006 %put &&x;
00007

```

Line	Comment
00003	Only the first argument is in quotes. Argument two references a data set variable 'y' with value 'Monday'. Argument one creates a macro variable 'x' with the value <i>Monday</i> .

These are the four variations in the Call Symput routine.

Now note the timing of creating the macro variable with Call Symput.

```

Command Editor
00001 data _null_;
00002 z1 = 'January';
00003 call symput('month',z1);
00004 %put &&month;
00005 run;
00006
00007 %put &&month;
00008

```

Line	Comment
00004	The %put inside the Data Step will not resolve since the macro variable has not been created.
00007	The %put after the Data Step will resolve.

Using the Call Symput Routine

Application of the Call Symput routine displays its programming power.

To illustrate, let's create macro variables and values for frequencies of distinct values in a data set.

```

Command Editor
00001 proc freq data=work.dogsplus order=freq;
00002 table status / noprint out=work.state;
00003 (where=(status ne ""));
00004 keep=status count;
00005 run;
00006
00007 proc print data=work.state; run;
00008
00009 data _null_;
00010 set work.state;
00011 call symput(status, count);
00012 run;
00013
00014 %put &&state;
00015 %put &&state;
00016 %put &&state;
00017 %put &&state;
00018 %put &&state;
00019

```

Line	Comment
00011	Each loop of the incoming SAS data set work.state creates a new macro. The macro name is determined by the value in the status variable. The macro value is determined by the value in the count variable.

Analyze the following additional programs to see the power of the Call Symput routine.

Example 1:

Create output as shown. It requires both a string and numeric value reflecting the average salary of the data set.

Format the string to use in a title statement.

Use the numeric value in a Where statement to subset the top half earners into a new data set.

Line	Comment
00001-00004	Proc Means is used to calculate the mean of the variable salary. An output data set is created (work.summary) with a variable (meansal) that is the mean of salary.
00006-00010	The data step is used to read in the data set created by Proc Means. Call symput is used to create macro variables meansal and avgsal.
00012	Macro variable avgsal is used in Title statement.
00016	Macro variable meansal is used in where clause to subset data.

AGE	NAME	STAFFNO	SALARY
1	Julia Pendlebury	0052	925,410.00
2	Heleen Clindorfard,	0053	925,710.00
3	Mark Chapai	0010	925,384.00
4	Julie Jennings	0024	925,740.00
5	David Duitly	0028	925,790.00
6	Dawn Duvet	0026	925,078.00
7	Brian Elissa	0029	925,000.00
8	Dorabrah Seiling	0071	931,604.00
9	Taranee Larter	0010E	930,200.00
10	Arian Pestiethwaite	0019	925,700.00
11	Chila Frembody	0025	923,023.00
12	Agnes Fortuesque-Smyt	0061	925,410.00
13	Steven McGrath	0017	925,070.00
14	David C. Anderson	0079	922,556.00
15	Etaine M. Nigh	0080	925,050.00
16	Sam H. Flesch	0072	927,000.00
17	Dorabrah Randolph	0077	927,850.00
18	Lois Barr	0025	925,000.00
19	Mark Hancini	0010I	925,600.00
20	Fanele Hiant	0029	925,050.00

Example 2:

Create macro variables to show average age by gender values. Show one average age for males, another for females.

```
00001 proc sort data=work.demogus;
00002   outsort=demogus;
00003   by gender;
00004 run;
00005 proc means data=work.demogus mean noprint;
00006   var age;
00007   by gender;
00008   output out=work.agestate (keep=gender mean
00009     mean=age;          where=(gender ne ""));
00010 run;
00011 data _null_;
00012   set work.agestate;
00013   call symput(gender||'||mean');
00014 run;
00015 xput age=age;
00016 xput age=age;
```

Line	Comment
00001-00003	The data set saved.demogius is sorted by gender.
00006-00012	Proc Means calculates the mean age for each gender. An output data set is created (work.agestats) with two observations; the first with the mean age for Females and the second with the mean age for Males.
00014-00017	The data step reads in the data set containing the mean age values. Call symput is used to create a macro variable. The name of the macro variable is given by the value of the gender variable. The value of the macro variable is given by the value of the variable mean. Because there are two observations in work.agestats, two macro variables are created, one for Females and the second for Males.
00019-00020	%put is used to write the value of the macro variables to the Log

```

C:\log (Untitled)
Command ==>
00
01  Xput ###f###;
02  ###37.2    ##
03  Xput ###n###;
04  ###38.78125  ##

```

Example 3:

The idea is to archive observations more than 30 days old. This example could be adapted to any dynamic file (say one under FSEDIT control) where it was important to move old observations into some archive or backup file.

```

00001  data work.new;
00002  input @1 data      data2.
00003         reading1
00004         reading2;
00005  datalines;
00006  01may1988      102    158
00007  02aug1988      88    148
00008  05may1987     120    39
00009  01aug1988      33    85
00010  11may1988     13    67
00011  run;
00012
00013  data work.coldrecs;
00014  set work.new
00015     if today() - data > 30 then output work.coldrecs;
00016  run;
00017
00018  data _null_;
00019  set work.coldrecs nobs=nobs;
00020  call symput('append',cat(nobs));
00021  stop;
00022  run;
00023
00024  %xerox archive;
00025  %if %append ne % then %do;
00026  %proc append base=teved.arch data=work.coldrecs;
00027  %run;
00028  %mend;
00029  %xerox %put No archiving required;
00030  %xerox archive;
00031
00032  %archive;
00033
00034

```

Line	Comment
00001-00011	Create original data set.
00013-00016	Create work.oldrecs with observations more than 30 days old.
00018-00022	Use data set option NOBS to create variable NUMOBS. The value of NUMOBS is the number of observations in data set work.oldrecs. Call symput is used to create a macro variable (append) with the number of observations in the data set work.oldrecs.
00024-00030	Macro bundle archive is created. If the value of the append macro is not zero (therefore there are observations in the work.oldrecs data set) the Proc Append code is generated and executed. Otherwise the Proc Append code is not generated and executed.

Example 4:

Subset a data set so that each distinct value of a variable is written to a new data set bearing the value name.

```

00000  Command end;
00001  Xmacro split {inputde, byvar, prefix};
00002
00003  Xs Create a list of distinct values of the byvar;
00004  proc freq data=;inputde;
00005  tables byvar / noprint outsmk=work.numbye {keep=abyvar};
00006  run;
00007
00008  Xs Create a series of macro variables with count values;
00009  data _null_;
00010  set work.numbye end=;
00011  call symput('nvar'||int(put(_n_,E.)),
00012            int(put(abyvar,3.)));
00013  if x then call symput('numbye'||put(_n_,E.));
00014  run;
00015
00016  Xs Use the Data Step to name new data sets and subset;
00017  data
00018  Xdo i=1 Xto numbye;
00019  Xsref Xsabyvar=i
00020  Xend;
00021
00022  set &inputde; i
00023  Xlist &abvar;
00024  Xdo j = 1 Xto numbye;
00025  Xsref i= &abyvarXsabyvar=i then output &prefXsabyvar=i;
00026  Xlist &abvarXsref;
00027  Xend;
00028  run;
00029
00030  Xmacro split;
00031
00032  Xsplit (saved.bpl, patient, de)
00033

```

Line	Comment
00004-00006	Use Proc Freq to create a data set containing all unique values of variable defined by &byvar.
00009-00014	Create a series of macro variables called mvar1, mvar2, etc. The values of these macros are given by the value of the macro &byvar. The macro variable Numobs that is created has a value equal to the number of unique values of &byvar.
00017-00021	Use a %do loop to create the data set names in the data statement.
00023	Create macro variable else and set its value to null
00024-00028	Use a %do loop to generate a series of if, else if statements. Based on the value of &byvar the observation is written to the appropriate data set.

Example 5:

Let us assume that the programmer wants a title statement to spell out the results determined from data set summarization.

For example, if there are more males in the population than females, the title should read, "Males outnumber Females". If the reverse is true, the title should read, "Females outnumber Males". How can the programmer tell SAS which title to select?

```

Program Editor m12.11
Command ==>
00001 %macro males;
00002   title 'Males outnumber Females';
00003   title2 "&m to &f";
00004   %let order = descending;
00005 %mend males;
00006
00007 %macro females;
00008   title 'Females outnumber Males';
00009   title2 "&f to &m";
00010   %let order = ;
00011 %mend females;
00012
00013 %macro size;
00014   %global order;
00015   options nodata nonumber;
00016   title;
00017
00018   data _null_;
00019     set saved.demoglus (keep = gender
00020                       where =(gender ne " "));
00021     end=end;
00022     retain f m ;
00023     if gender = "F" then f+1;
00024     else m+1;
00025
00026     if end then do;
00027       call symput(gender, compress(put(f, 3.)));
00028       call symput(gender, compress(put(m, 3.)));
00029     end;
00030   run;

```

```

Program Editor m12.11
Command ==>
00032   %if &m gt &f %then %males;
00033   %else %females;
00034
00035   proc sort data=saved.demoglus
00036     out=work.demoglus;
00037     by &order gender;
00038   run;
00039
00040   proc print data=work.demoglus;
00041   run;
00042
00043 %mend size;
00044
00045 %size

```

Line	Comment
00001-00005	The %macro - %mend bundle <i>males</i> supplies the title to use if males outnumber females. If so, the data set is sorted in descending order to show the males at the top. The second title statement will show the actual values (derived below).
00007-00011	The %macro - %mend bundle <i>females</i> supplies the title to use if females outnumber males. If so, the data set is sorted in ascending order to show the females at the top. The second title statement will show the actual values (derived below).
00014	The %global statement creates a slot for the <i>order</i> macro. The value is supplied when the macro %male or %female is invoked conditionally below.
00016	Because titles are used, all previously existing titles are removed.
00022-00025	The <i>sum statements</i> F+1 and M+1 count the number of observations read into the Data Step.
00027-00029	The <i>Call Symput</i> routines create macro variables <i>F</i> and <i>M</i> at the end of the data step execution.
00033-00035	The %if...%then condition invokes either %males or %females based on values of the macro variables. At this point the title statements are ready and the Global Symbol Table holds a value of either <i>descending</i> or <i><null></i> for the macro variable <i>order</i> .
00039	The <i>order</i> macro variable resolves from the Global Symbol Table.

Frequently Asked Questions About Call Symput

(a) To which symbol table does the macro variable belong?

Most macro variables created by the use of the Call Symput routine are placed in the global table. However, the variable will be placed in the nearest symbol table in the current referencing environment of the data step, providing that symbol table is not empty. If it is empty, it will be placed in the next higher symbol table, providing it is not empty and so on.

(b) When is the macro variable available for use?

The most common mistake with the use of the Call Symput routine is to forget that the macro variable is *only available after the data step completes execution!*

(c) How does the Call Symput format character values?

The default format is \$w. where w is the width of the variable. Hence trailing blanks may also be transferred. Avoid this by the use of the trim function with the second argument:

```
call symput('mvar1', trim(datavar));
```

(d) How does Call SYMPUT format numeric values?

The default format is BEST12. with the number being right justified. You may need to use the left and put functions to get your desired result:

```
call symput('mvar1', left(put(datavar, 3.));
```

Symget Function

The purpose of the *Symget* function is to pass values from a symbol table in the current referencing environment to the data step variable in the program data vector:

Symbol Table

mvar1	Value1
mvar2	Value2

Program Data Vector

VarA	VarB	VarC	VarD	VarE
	Value2			

Note several important features about the *Symget* function:

- It is used exclusively in the data step.
- It works at data step execution time (not compile time).
- *Symget* always retrieves a character variable.
- The data step variable created by *symget* is a character string with a default length of 200.

The syntax for the *symget* function is:

```
Variable=symget(argument);
```

Three types of arguments are accepted by *symget*:

- Name of a macro variable in single quotes.
- A data step character variable whose value is the name of a macro variable.
- A data step character expression.

Use of the *Symget* function is quite versatile.

```

Command ===>
00003 xlet value=M;
00004 xlet title="Mr.";
00005
00006 data work.demoglus;
00007   set saved.demoglus (where=(status=symget('value')));
00008   if gender = symget('value') then title = symget('title');
00009 run;
00010
00011 proc print data=work.demoglus;
00012   var status gender title;
00013 run;

```

Line	Comment
00007	The <i>Symget</i> function used in a where option
00008	The <i>Symget</i> function used in a conditional assignment

In contrast, consider the following attempt to use the *Symget* function.

Warning: This program contains syntax errors!

```

Command ===>
00001 xlet value=M;
00002 xlet title="Mr.";
00003
00004 data symget('value');
00005   set saved.demoglus (where=(status=symget('value')));
00006   if gender = symget('value') then title = symget('title');
00007 run;
00008
00009 proc print data=symget('value');
00010   var status gender title;
00011   where status = symget('value');
00012 run;
00013

```

Line	Comment
00004	The <i>Symget</i> function is incorrectly used to name the data set (which is done at compile time).
00009, 00011	The <i>Symget</i> function incorrectly used outside the Data Step.

The Log window shows several problems.

```

NOTE: The SAS System stopped processing this step because of errors.
NOTE: DATA statement used: 2.52 seconds
real time

NOTE: The SAS System stopped processing this step because of errors.
NOTE: PROCEDURE PRINT used: 1.39 seconds
real time

```

How might the problem in the above syntax be solved?

```

Command ===>
00001 xlet value=M;
00002 xlet title="Mr.";
00003
00004 data _value_;
00005   set saved.demoglus (where=(status=symget('value')));
00006   if gender = symget('value') then title = symget('title');
00007 run;
00008
00009 proc print data=_value_;
00010   var status gender title;
00011   where status = "&value";
00012 run;
00013
00014

```

Line	Comment
00004, 00009, 00011	Unlike the <i>Symget</i> function, invoking a macro variable value using <i>&value</i> does not depend on the Data Step nor on execute time.

Dynamic Change to the Macro Variable Name

The most common use of the *Symget* function is to make dynamic changes to the macro variable name.

```

Command ===>
00001 xlet mvar1 = first;
00002 xlet mvar2 = second;
00003 xlet mvar3 = third;
00004
00005 data work.newsds;
00006   do i = 1 to 3;
00007     datavar = symget('mvar'||put(i,1.));
00008     output;
00009   end;
00010 run;
00011
00012 proc print data=work.newsds;
00013 run;

```

Line	Comment
00001-00003	The three %let statement created sequentially named macro variables.
00006-00009	The do...to; end; syntax provides the numbered portion of the macro variable names.

The distinction between the two syntax options of the Symget function is in the use of quotes!

Placing the first argument in quotes indicates a literal; the string inside the quotes is the macro variable name.

When the first argument is not in quotes, it indicates a data set variable; the value of the data set variable supplies the name of the macro variable.

Creation of Numeric Variables

Another point to note is that the Symget function creates a macro that is a character string. What are the implications of this?

Consider the following syntax that appears to be quite similar. The syntax uses the input function to convert a character variable to a numeric variable.

```

Command (xxx)
00001 /***** General Use of the Input Function *****/
00002 data changes;
00003   input a b;
00004   x = input(a,T.);
00005 datalines;
00006 1234567
00007 8901
00008 7
00009 run;
00010
00011 proc contents data=changes; run;
00012 proc print data=changes; run;
00013
00014 /***** Input Function with Symget *****/
00015
00016 %let scale = 20;
00017
00018 data justify;
00019   cost1 = input(&scale,T.);
00020   cost2 = input(symget('scale'),T.);
00021   cost3 = input(&scale,T.);
00022   cost4 = input('20',T.);
00023 run;
00024
00025 proc contents data=justify; run;
00026 proc print data=justify; run;
00027
00028

```

Line	Comment
00020-00023	The derived variables cost1 to cost4 seem to follow the same syntax. They do not. Explore the differences in the Input statements below.

Why these differences in results?

Remember that the Input function uses a character value as the first argument. Both Symget and '20' provide the correct variable type, and thus the correct justification (to the left). These two examples work as predicted.

In contrast, &scale and 20 are numeric values. The Log window states that numeric values have been converted to character. However, the automatic conversion used the Best12. format. As a result, the numbers were converted to strings as " 20". What part of the string contributed to the values of cost1 and cost3? Answer: the first two (blank) spaces. As a result, the values for cost1 and cost3 are missing.

Remember the result from the Symget function is a character string of default length 200. It will be left justified and therefore works as a literal string.